

**For EMC/EMI and other instrumentation applications.** Provides 500 watts of power in the 8.0 to 18.0 GHz frequency band in a compact 19-inch rack-mount dual drawer configuration for wideband testing.

### Efficient and Reliable

Employs CPI dual-depressed collector helix traveling wave tubes, increasing efficiency by a nominal 20% over conventional single collector TWTs, and a power supply designed with a minimum number of parts for maximum uptime.

### Simple to Operate

Integrated microprocessor control lets the user adjust and monitor all operating parameters from one easy-to-read local or remote panel, using straightforward menu-driven commands. Includes a built-in interface and serial bus for operation from the station computer.

### Meets Global Requirements

230 VAC operation. Meets International Safety Standard EN-60215, Electromagnetic Compatibility 2014/30/EU and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements. CE Marked.

### Worldwide Support

Backed by over 40 years of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.



CPI 500 W M-band TWT, Model VZM2780C2


### OPTIONS:

- Mimic remote control panel
- External harmonic filters
- External output isolator
- Ethernet interface

Quality Management  
System - ISO 9001:2015



Specification	CPI Model VZM2780C2, 500 W M-Band Rack Mount TWTA
Output Frequency	8.0 to 18.0 GHz
Output Power (min.) TWT Flange	550 W min. 500 W min.
Gain	57 dB at rated power output, 57 dB typ. at small signal
RF Level Adjust Range	0 to 20 dB
Output Power Adjustability	±0.1 dB
Gain Stability	±0.25 dB/24 hour typ, at constant drive and temperature, after 30 minute warmup
Small Signal Gain Slope	0.02 dB/MHz max.
Gain Variation	10 dB pk-pk typ. over the 10 GHz bandwidth
Input VSWR	1.5:1 max.
Output VSWR	2.0:1 max.
Load VSWR	2.0:1 for full spec. compliance; any value operation without damage
Residual AM	-45 dBc up to 4 kHz; -20 [1.25 + logF (kHz)] dBc, 4 kHz to 500 kHz; -80 dBc above 500 kHz
Noise and Spurious	-60 dBW/4 kHz
Harmonic Content	-6 dBc typical at 8 GHz
Primary Power	Voltage: Single phase, 208-120 VAC ±10%, or 380-415/220-240 VAC ±10%; 5 wires are: phase 1, 2 & 3, neutral and ground (wire 5 can be used if available); Frequency: 47-63 Hz, 15 A max.
Power Factor	0.90 min. at 50 Hz
Power Consumption	6.9 kVA typ, 7.5 kVA max.
Inrush Current	200% max.
Ambient Temperature	-10°C to +40°C operating, -20°C to +70°C non-operating
Relative Humidity	95% non-condensing
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft. operating; 50,000 ft. non-operating
Shock and Vibration	As normally encountered in a protected engineering laboratory environment
Cooling	Forced Air with integral blower. Rear air intake and exhaust. Maximum external pressure loss allowable: 0.5" water column
Connections	RF Input: Type N Female; RF output: WRD-750 waveguide; RF output monitors: Type N Female, -50 dB nom.
M&C Interface	Serial RS232 or RS422/485 (Ethernet optional)
Dimensions, W x H x D	RF Drawer: 19 x 17.5 x 28 inches (483 x 445 x 711 mm); Power Supply: 19 x 8.75 x 24 inches (483 x 223 x 610 mm)
Weight	RF Drawer: 180 lbs (82 kg) nom; Power Supply: 100 lbs (45 kg); Interconnect Cables: 10 lbs (4.5 kg)
Acoustic noise	72 dBA @ 1 meter from front panel



**SMP Division**  
**Satcom Products**  
tel: +1 (905) 702-2228  
email: [satcommarketing@cpii.com](mailto:satcommarketing@cpii.com)  
web: [www.cpii.com/satcom](http://www.cpii.com/satcom)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

© 2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.