

Antenna Measurement Systems - x250 Series

Features and Specifications



DAMS 5250 - DC to 6 GHz

DAMS 6250 - DC to 18 GHz

DAMS 7250 - DC to 40 GHz

System Features

Wide Frequency Ranges

Capable of measuring ranges from DC to 6 GHz (*DAMS 5250*), DC to 18 GHz (*DAMS 6250*) or DC to 40 GHz (*DAMS 7250*).

Dual-Axis Movement

360° azimuth range with up to $\pm 90^\circ$ of elevation tilt.

High Resolution

Capable of .25° steps azimuth and .25° steps elevation (*DAMS 5250*), or up to .10° steps azimuth and .10° steps elevation (*DAMS 6250/7250*).

Weight Capacity

Able to carry payloads of up to 150 lbs.

Precision Rotary Joint

The rotary joint is constructed from a special carbon based material that allows noiseless measurements up to 6 GHz (*DAMS 5250*), 18 GHz (*DAMS 6250*) or 40 GHz (*DAMS 7250*).

Deluxe Measurement Software

All systems come complete with DAMS Measurement Studio which features various special plots and functions (*DAMS Measurement Studio Pro included with DAMS 6250/7250*).

Spherical Plot Module

Map measured antenna data over a sphere or an ideal isotropic sphere (*DAMS 6250/7250 only*).

Complete Warranty

Our 3-year warranty covers all parts, labor and technical support.

Included RF Cables

All systems include two 10' calibrated measurement cables. Precision low-loss SMA cables (*DAMS 5250*), precision ultra-low-loss SMA cables certified to 18 GHz (*DAMS 6250*) or precision low-loss cables with 2.92mm "K" connectors certified to 40 GHz (*DAMS 7250*).

Includes All Accessories

This is the complete measurement solution and includes everything besides the VNA and computer (*DAMS 6250/7250 only*).

Precision Drive Train

Steel gear and worm, with ball and tapered roller bearings for high torque and smooth motion.

Advanced Measurement Calculator

Takes the hassle out of performing detailed and complex computations.

Positioner Specifications

Platform Operating Specifications

Frequency Ranges:	DC to 6 GHz (<i>DAMS 5250</i>) DC to 18 GHz (<i>DAMS 6250</i>) DC to 40 GHz (<i>DAMS 7250</i>)
Platform Movement:	Horizontal 1.8 degree precision stepper motor with low-noise belts Up to .10° azimuth resolution 360° continuous azimuth range ± 90° elevation range at 0.1° per step
Drivetrain:	Heavy-duty steel gear drive-train Steel gear and worm, with ball and tapered roller bearings
Positioner Feedback:	Precision potentiometer (<i>DAMS 5250</i>) High accuracy resolver (<i>DAMS 6250/7250</i>)
Platform Max Speed:	30 R.P.M. azimuth 120° per minute elevation
Platform Mounting:	30" aluminum AUT thrust plate with 250 lbs. of payload capacity Ultra heavy-duty tripod
Weight Capacity:	250 lbs. maximum payload at level position (capacity decreases with angle)
Cable Interface:	Ultra high-quality cable with SMA connectors Ultra-precision, low-noise rotary joint with SMA connectors (<i>"K" connectors on DAMS 7250</i>)
Included Options:	Digital level for precise setup Positioning laser for long range alignment DAMS Software Studio Pro Advanced processing module 3-year warranty on parts and labor Technical support

Controller Operating Specifications

Control Methods:	DAMS Antenna Measurement Software (or any software with serial communication, which requires Platform Development Kit)
Interface:	USB/RS-232 serial/ethernet
Power Requirements:	+48 vDC (6.0A)
Analyzer Interface:	GPIB controller card (not included)

Physical Properties

Positioner Dimensions:	17 inches (30.5 cm) wide 12 inches (12.5 cm) deep 17 inches (35.6 cm) tall
Height:	5" (12.5 cm) without vertical movement assembly or tripod 35" (35.6 cm) minimum with vertical movement assembly and tripod 72" (182.88 cm) maximum
Weight:	120 lbs. (positioner only) 35 lbs. (tripod only) 155 lbs. (combined weights)
Positioner Composition:	Aluminum 80% Stainless steel 15% Misc. plastics/metals 5%
Tripod Composition:	Aluminum and plastic

Environmental Specifications

Operating Temp:	0° C to 45° C (32° F to 104° F) (with no condensation)
Transport Temp:	-40° C to 60° C (-40° F to 140° F) (no condensation within 72 hours)

Overview of Software Features

Multi-Trace Plots (Polar/Amplitude)

- Compare multiple antennas
- Dual marker function
- Selectable linear or log (dB)
- Instant delta dB/angle marker readout
- Selectable scale
- Export option

3D and Spherical Plots

- Full 3D interface
- Map data onto a sphere
- Plot data at any frequency
- Multiple overlay and display features
- Support for power meters, voltmeters, spectrum analyzers and VNA/PNA's
- Continuous rotation or swept measurements
- Export data with variable formatting
- Measure up to 1600 frequency points per increment
- Variable speed
- Move to max signal position
- Vertical/horizontal scan measurements
- CW/CCW antenna rotation

Other Features

- Calibrated horn table import
- Path loss calculator
- Complete data manipulation
- Multiple storage registers for convenience
- Link commander (link simulator)
- Complex data calculator

Optional Extras

- Antenna Network & Measurement Simulator

