Data Sheet

VC-06 HD Color Video Camera

Product Overview

The TDK VC-06 High Definition Color Video Camera is a high performance RF shielded CCTV video camera system designed for remote monitoring of equipment under EMC testing. The camera is also ideal for wide angle anechoic chamber monitoring, shielded access control, and test action archiving.

Designed for EMC Testing

The VC-06 is a video camera designed to operate in the harsh environments required by EMC testing. The camera is housed in an EMI hardened protective case, and the control and video signals use fiber optics to prevent interference caused by high electromagnetic fields present during EMC testing. The all-digital, high-definition VC-06 is remotely focused, positioned and zoomed using the required TDK SI-300CC-HD Camera Controller.

Camera Features

- 1920x1080, 60 fps, High Definition
- Zoom: 30x Optical, +12x Digital
- Low Light Sensitivity: 0.5 lux without ICR (night vision) and 0.095 with ICR
- EMI Shielded to >200 V/m (DC to 18 GHz)
- Shielded 12 VDC or universal AC adapter operated
- One fiber optic cable for Audio/Video/ Control
- Pan/Tilt mechanism
- Remote control for Pan, Tilt, Focus, Zoom, Iris Control
- Color Enhancement
- Image Enhancements: E-flip, Black & White, and Mirror Image



The TDK VC-06 High Definition Color Video Camera is an RF shielded CCTV designed specifically for remote monitoring of equipment during EMC testing in a shielded room or anechoic chamber.

Options

- Audio Monitoring
- DC battery power
- VCMS-150R Video Camera Monopod Stand
- VCWM Video Camera Wall Mount



The TDK SI-300CC-HD Camera Controller is capable of controlling up to four VC-06 cameras when optioned with additional video ports. It comes standard with one video port.



VC-06 HD Color Video Camera

Optical Capabilities

Resolution: 1920x1080, 60 fps

Image Sensor: 1/2.8" with approx.

3.27 Mega pixels

Zoom: 30x Optical zoom

+12x Digital zoom

Angular Field of View: 55.4° wide; 2.9° tele-

photo

Min. Object Distance: 10 mm (wide);

1000 mm (telephoto)

Iris Control: Manual and

Automatic

Color Balance: Automatic Synchroniza-

tion

Angle of Pan/Tilt: Pan: +/- 170°

Tilt: +/- 90°

Fiber Optic Cable: One duplex cable

Video Output: HDMI or SDI

Minimum Illumination: 0.5 lux

Environmental Specifications

Operating temperature: 0° to $+30^{\circ}$ C Storage Temperature: -10° to $+50^{\circ}$ C

Overall Dimensions

With Pan/Tilt unit: $10'' \text{ H} \times 11'' \text{ D} \times 3.75'' \text{ W}$

 $(25.4 \text{ cm} \times 27.9 \text{ cm} \times 9.5 \text{ cm})$

9.2 lbs (2.81 kg)

Without Pan/Tilt unit: $3.95'' \text{ H} \times 10'' \text{ D} \times 3.75'' \text{ W}$

 $(10 \text{ cm} \times 25.4 \text{ cm} \times 9.5 \text{ cm})$

3.2 lbs (1.45 kg)

Ordering Information

Product: Video Camera

Model Number: VC-06

Warranty: 1 year

To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd. Cedar Park, Texas 78613 USA

Phone: 1-512-258-9478
Fax: 1-512-258-0740
E-mail: info@tdkrf.com

Website: www.tdkrfsolutions.com



www.tdkrfsolutions.com