

## DYNAMITE 111

- **Maximum dry adhesion**
- **Prevents seam spreading and curling**
- **Strong wet tack**
- **Non-Strippable**

**Dynamite™ 111 Heavy Duty Clay Non-Strippable Wallcovering Adhesive** contains high solids to assure fast grab and a strong, durable bond. This adhesive is ideally suited for all heavy and difficult-to-install wallcoverings such as Commercial Type III vinyl, heavyweight fabric, flexible wood, Mylar® and foil. Cleans up with water while wet.

- Superior final bond
- Prevents seam spreading and curling
- Ideal for dry hanging paper-backed foils, Mylar® and fabrics

**SURFACE PREPARATION:** Surface must be clean and free of oil, dust, dirt, grease, mildew, and other foreign matter. For best results, use Dynamite All-Purpose cleaner to prepare walls. A diluted household bleach solution also works well to clean walls. Repair or fill cracks in wall with Dynamite Non-Shrink Spackling prior to priming. Plaster – New plaster must age at least 30 days before hanging wallcovering. Prime with Dynamite 221 or 222. Drywall – New drywall must be wiped down with a damp cloth to remove dirt, grease, wax and peeling paint. Prime with Dynamite 221 or 222. Other Porous Surfaces – Walls must be clean, dry, smooth and structurally sound. Prime with Dynamite 221 or 222. Glossy Surfaces – Ceramic tile, glossy paint, existing vinyl wallcoverings, Formica®, glass, plastic or baked enamel should be primed with Dynamite 221, 222 or 235. Commercial Grade II & III – Prime with Dynamite 235 when hanging heavy weight commercial-grade papers **DO NOT USE OVER OIL/ALKYD PAINT/PRIMER OR VARNISH UNLESS IT IS PRIMED WITH A DYNAMITE ACRYLIC PRIMER.**

**APPLICATION:** Mix well before using to ensure even consistency. For lightweight wallcoverings, thin as needed, up to 1 pint of water per gallon. Apply evenly, making sure sufficient adhesive is on edges and corners. Apply to wallcovering with a roller or stiff brush. Allow proper booking time according to manufacturer's instructions. **IMMEDIATELY** remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. **HANG WALLCOVERING ACCORDING TO MANUFACTURER'S INSTRUCTIONS.**

**COVERAGE:** Five gallons of adhesive will hang up to 40 single rolls. (1,400 sq. ft./5 gal.). Coverage rates can vary depending on condition of the substrate, priming and sizing, weather conditions and method of application.

**CLEAN-UP:** Immediately remove adhesive from face of washable wallcoverings and adjacent surfaces with a clean, wet sponge. Dry with a clean, lint-free towel to check for paste residue. Clean equipment with water.

**STORAGE:** Non-Strippable Heavy Duty Clay Wallcovering Adhesive should be stored at temperatures between 40°F and 100°F. Protect from freezing.

©2006 Gardner-Gibson, Inc.  
Manufactured by:  
Gardner-Gibson, Inc.  
P.O. Box 5449  
Tampa, FL 33675

See MSDS for more info

### TYPICAL PHYSICAL & PERFORMANCE CHARACTERISTICS

Weight per Gallon	10.5 LB
Color	Light Tan
Odor	Mild
Viscosity	28,000-32,000
pH	6.0 to 6.5
Open Time	Approx. 20 mins.
Resistance to mold & mildew	Excellent
Freeze-Thaw Stability	Yes
% Solids	51% +/- 2%
Recommended Storage Temperature:	40 F to 100 F.
Recommended Application Range	45 F to 100 F.
Flash Point	None
Shelf Life	12 months

### Approx. Shipping Weights: (Note: All approx. weights include container.)

1 gallon (3.8L)	11.0 lbs.
5 gallons(18.9L)	55.0 lbs.

### **CAUTION! DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.**

Eye, skin and respiratory irritant. In case of contact with eyes, flush with plenty of warm water. Persons with skin or respiratory sensitivity should not use product without sufficient protection. Avoid prolonged breathing of vapor or spray mist. Use only with adequate ventilation. In case of irregular or stopped breathing, administer oxygen and/or give artificial respiration. Get medical attention immediately. Contact with skin should be followed by washing with soap and water. If swallowed, do not induce vomiting. Call physician immediately. Seal container when not in use. When transporting product, be sure lid is tight and product is kept upright and secure. Do not store/warehouse product below 32°F.

**WARNING:** This product contains a chemical known to the State of California to cause cancer. Keep container closed when not in use.

VOC: 3.5 g/L

### **INGREDIENTS: (>1% OF TOTAL WEIGHT):**

CLAY (1332-58-7), DEXTRIN (9004-53-9), SODIUM NITRATE (7631-99-4), WATER (7732-18-5)

**QUALITY PROMISE:** Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. **THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.**