

ROMAN™

THE NO.1 CONTRACTOR BRAND

Technical Data: ECO-988

Updated: 1/16/18



ECO-988

Pigmented Wallcovering Primer

Pigmented Wallcovering Primer

Product Number(s): 11605, 11601

Base: 100% Acrylic Resin

Product Information

General Properties: The first part of a two-part system. Must be used in conjunction with ECO-788 Clay or ECO-888 Clear Wallcovering Adhesives for desired results.

- For desired results use with ECO-888 Clear or ECO-788 Clay Wallcovering Adhesive
- Superior white hiding power
- Water-resistant for double cutting
- Promotes strippability
- LEED compliant
- NSF/ANSI 342 compliant

Recommended Uses: For use with all types and weights of wallcovering

Compatible Coatings: For desired results, ECO-888 Clear or ECO-788 Clay Wallcovering Adhesive must be used.

Substrates: Apply over new, bare drywall

Mildew-Resistant: All Roman products contain biocides for in-can preservation

Specification Data

Coverage: Up to approx. 400-450 square feet per gallon

VOC (actual/regulatory): 0% / 0 g/L as calculated per EPA Method 24

Storage: Avoid freezing; keep in cool, dry place.

Drying Time: Typically dry-to-touch in approximately one hour and ready to hang wallcovering in three hours. Drying time will vary depending on the temperature, ventilation and humidity of the room.

Roman Decorating Products – Calumet City, Illinois

For Technical Help: Call 1-800-488-6117 or Email: technicalhelp@romandec.com

www.romandecoratingproducts.com

ROMAN™

THE NO.1 CONTRACTOR BRAND

Technical Data: ECO-988

Updated: 1/16/18

Application Instructions

Surface Preparation: Surface must be free from mold, mildew, grease and other residues, dry, smooth and structurally sound. Refer to the www.epa.gov website for removing mold and/or mildew. Before proceeding with any unusual conditions, consult your adhesive or wallcovering supplier.

Tinting: Can be tinted with universal tints; 4 oz. per 1 gallon maximum

Dilution: Do not dilute.

Application Method: Use only when the room temperature is above 50°F. Apply at recommended spread rate using a brush, roller, or spraying system. Do not overspread.

Airless Spray:	PSI Capable:	minimum 3000 psi
	Hose:	3/8" I.D.
	Tip Size:	.015 and larger
	Gun psi:	2000-2300

Clean-Up: Before the primer dries, remove the excess with clean water. Brushes and rollers should be cleaned immediately after use with warm, clean water.

Warning

If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead.

Roman Decorating Products, LLC does not endorse the use of any product in an installation that does not meet a Class A fire rating or any applicable code. Testing by a certified laboratory should be conducted to verify that the installation meets a Class A fire rating and to guarantee compliance with all applicable codes. Specifically, if a Roman product is used to hang wallpaper over existing wallpaper, it is unlikely to meet these standards.

Limited Warranty

Roman Decorating Products, LLC warrants that it will replace this product free of charge, if, within 12 months of manufacture, it is found to be defective in material or workmanship. This warranty is in lieu of any other. The exclusive remedy is limited to the replacement of the product and Roman disclaims all liability for consequential, punitive, and special damages. Conditions of use are beyond our control.

Caution

Store in a cool, dry place. DO NOT FREEZE! Do not take internally. In case of ingestion, seek medical attention. Avoid contact with skin and eyes. Use of skin and eye protection is recommended at all times. If contact with eye occurs, flush with water for 15 minutes. If skin contact occurs, wash with soap and water. Seek medical attention if rash or other symptoms occur. Do not mix with other chemicals. Use in a well-ventilated work area. Close container after each use. Keep out of reach of children.