

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations
Revision Date: 05/06/2019

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture

Product Name: StaticSmart SDT+

Intended Use of the Product

Use of the Substance/Mixture: No use is specified.

Name, Address, and Telephone of the Responsible Party

Company

United Static Control Products Inc.

4301 32nd Street W. B-20

Bradenton, FL 34205

719 676 3928

www.unitedscp.com

Manufacturer

Helmitin Inc.

11110 Airport Road

Olive Branch, MS 38654

Phone: 877.823.2624

www.helmitin.com

Emergency Telephone Number

Emergency Number : CHEMTREC 1-800-424-9300

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Not classified

Label Elements

GHS-US Labeling No labeling applicable

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)
Graphite*	(CAS No) 7782-42-5	15 - 40
Titanium dioxide*	(CAS No) 13463-67-7	10 - 30

*This product contains a material that may be hazardous when present as an airborne dust. Since this product is in a liquid form, the material is not able to become airborne and cannot be inhaled. Thus, the hazards usually associated with this material are not applicable to this product.

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

Skin Contact: Rinse immediately with plenty of water. Remove contaminated clothing. Rinse affected area with water for at least 5 minutes. Obtain medical attention if irritation develops or persists.

Eye Contact: Rinse cautiously with water for at least 5 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention if redness, pain, or irritation occurs.

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

Most Important Symptoms and Effects Both Acute and Delayed

General: Not expected to present a significant hazard under anticipated conditions of normal use.

Inhalation: Prolonged exposure may cause irritation.

Skin Contact: Prolonged exposure may cause skin irritation.

Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Hazardous Combustion Products: Carbon oxides (CO, CO₂). Oxides of titanium.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clean up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific End Use(s)

No use is specified.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

For substances listed in section 3 that are not listed here, there are no established Exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), OSHA (PEL), Canadian provincial governments, or the Mexican government

Graphite (7782-42-5)		
USA ACGIH	ACGIH TWA (mg/m ³)	2 mg/m ³ (all forms except graphite fibers-respirable fraction)
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (synthetic-total dust) 5 mg/m ³ (synthetic-respirable fraction)
USA NIOSH	NIOSH REL (TWA) (mg/m ³)	2.5 mg/m ³ (natural-respirable dust)
USA IDLH	US IDLH (mg/m ³)	1250 mg/m ³
Alberta	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibres-respirable)
British Columbia	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibres-respirable)
Manitoba	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibers-respirable fraction)
New Brunswick	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except graphite fibres)
Newfoundland & Labrador	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibers-respirable fraction)
Nova Scotia	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibers-respirable fraction)
Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (synthetic-respirable mass) 10 mg/m ³ (synthetic, total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (synthetic-respirable mass) 10 mg/m ³ (synthetic, total mass)
Ontario	OEL TWA (mg/m ³)	2 mg/m ³ (except Graphite fibres-respirable)
Prince Edward Island	OEL TWA (mg/m ³)	2 mg/m ³ (all forms except Graphite fibers-respirable fraction)
Québec	VEMP (mg/m ³)	2 mg/m ³ (containing no Asbestos and <1% Crystalline silica, except Graphite fibres-respirable dust)
Saskatchewan	OEL STEL (mg/m ³)	4 mg/m ³ (natural, except Graphite fibres-respirable fraction)
Saskatchewan	OEL TWA (mg/m ³)	2 mg/m ³ (natural, except Graphite fibres-respirable fraction)
Yukon	OEL TWA (mg/m ³)	20 mppcf 30 mppcf (synthetic) 10 mg/m ³ (synthetic)
Titanium dioxide (13463-67-7)		
USA ACGIH	ACGIH TWA (mg/m ³)	10 mg/m ³
USA ACGIH	ACGIH chemical category	Not Classifiable as a Human Carcinogen
USA OSHA	OSHA PEL (TWA) (mg/m ³)	15 mg/m ³ (total dust)
USA IDLH	US IDLH (mg/m ³)	5000 mg/m ³
Alberta	OEL TWA (mg/m ³)	10 mg/m ³
British Columbia	OEL TWA (mg/m ³)	10 mg/m ³ (total dust) 3 mg/m ³ (respirable fraction)
Manitoba	OEL TWA (mg/m ³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m ³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m ³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m ³)	10 mg/m ³

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Northwest Territories	OEL TWA (mg/m ³)	5 mg/m ³ (respirable mass) 10 mg/m ³ (total mass)
Ontario	OEL TWA (mg/m ³)	10 mg/m ³
Prince Edward Island	OEL TWA (mg/m ³)	10 mg/m ³
Québec	VEMP (mg/m ³)	10 mg/m ³ (containing no Asbestos and <1% Crystalline silica-total dust)
Saskatchewan	OEL STEL (mg/m ³)	20 mg/m ³
Saskatchewan	OEL TWA (mg/m ³)	10 mg/m ³
Yukon	OEL STEL (mg/m ³)	20 mg/m ³
Yukon	OEL TWA (mg/m ³)	30 mppcf 10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Ensure adequate ventilation, especially in confined areas. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment: Protective goggles. Gloves. Protective clothing.



Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink or smoke during use

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Grey
Odor	: Low Odor
Odor Threshold	: Not available
pH	: 6.5 – 8.5
Evaporation Rate	: Same as water
Melting Point	: Not available
Freezing Point	: 32°F
Boiling Point	: ~212°F
Flash Point	: >200°F
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Same as water
Relative Vapor Density at 20 °C	: Not available
Relative Density	: Not available

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Specific Gravity	: 1.12
Solubility	: Water soluble
Partition Coefficient: N-Octanol/Water	: Not available
Viscosity	: 20,000 – 27,000 cps
Explosion Data – Sensitivity to Mechanical Impact	: Not expected to present an explosion hazard due to mechanical impact.
Explosion Data – Sensitivity to Static Discharge	: Not expected to present an explosion hazard due to static discharge.
VOC Content (SCAQMD Rule 1168)	: <1 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable under recommended handling and storage conditions (see section 7).

Possibility of Hazardous Reactions: Hazardous polymerization will not occur.

Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Incompatible materials.

Incompatible Materials: Strong acids, strong bases, strong oxidizers.

Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Oxides of titanium.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified

LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Not classified

Serious Eye Damage/Irritation: Not classified

Respiratory or Skin Sensitization: Not classified

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not classified

Carcinogenicity: Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: Prolonged exposure may cause irritation.

Symptoms/Injuries After Skin Contact: Prolonged exposure may cause skin irritation.

Symptoms/Injuries After Eye Contact: Prolonged exposure to liquid may cause a mild irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Titanium dioxide (13463-67-7)	
LD50 Oral Rat	> 10000 mg/kg
Urea (57-13-6)	
LD50 Oral Rat	8471 mg/kg
ATE US (oral)	8,471.00 mg/kg body weight
Titanium dioxide (13463-67-7)	
IARC Group	2B
OSHA Hazard Communication Carcinogen List	In OSHA Hazard Communication Carcinogen list.

SECTION 12: ECOLOGICAL INFORMATION

Toxicity No additional information available

Persistence and Degradability Not available

Bioaccumulative Potential

Mobility in Soil Not available

StaticSmart SDT+

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology – Waste Materials: Avoid release to the environment.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT Not regulated for transport

In Accordance with IMDG Not regulated for transport

In Accordance with IATA Not regulated for transport

In Accordance with TDG Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Graphite (7782-42-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
Titanium dioxide (13463-67-7)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard

US State Regulations

Proposition 65 – To the best of our knowledge, this product does not contain any of the listed chemicals, which the state of California has found to cause cancer, birth defects or other reproductive harm.

Graphite (7782-42-5)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List
Titanium dioxide (13463-67-7)
U.S. - Massachusetts - Right To Know List U.S. - New Jersey - Right to Know Hazardous Substance List U.S. - Pennsylvania - RTK (Right to Know) List

Canadian Regulations

Graphite (7782-42-5)
Listed on the Canadian DSL (Domestic Substances List)
Titanium dioxide (13463-67-7)
Listed on the Canadian DSL (Domestic Substances List)

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 05/06/2019

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2015