



ACCESSORIES:

- A. ONE(1) RF, SHIELDED PERSONNEL DOOR WITH 36" X 84" CLEAR OPENING, TYPE RCM-154.
- B. POLYVINYL AND MASONITE UNDERLAYMENT.
- C. ONE(1) BRASS GROUND STUD.
- D. ONE(1) DUAL (2-WIRE) 30 AMPERE POWER FILTER.
- E. TWO(2) RF, AIR VENTS (12" X 12").
- F. ONE(1) RF, PENETRATION PANEL (12" X 12").

NOTES:

- 1. PARENT ROOM FLOOR MUST BE FLAT AND LEVEL WITHIN $\frac{1}{2}$ " EVERY 10'-0" (NON-ACCUMULATIVE). NOT BY UNIVERSAL SHIELDING CORP. PARENT ROOM FLOOR, WALLS AND CEILING MUST BE FREE OF ANY OBSTRUCTIONS.
- 2. FINAL FABRICATION CANNOT BE COMPLETED UNTIL DRAWING(S) IS/ARE APPROVED BY CUSTOMER.
- 3. ALL ELEVATIONS ARE SHOWN FROM INSIDED OF RF, ENCLOSURE.

MATERIA -INISH

DRAWN USU
CHECKED DATE
APPROVED DATE

HEAT TREAT
RIGHT



UNIVERSAL
SHIELDING CORP

SIZE DRAWING NUMBER IS

C USC-