

UCS 200N

ULTRA COMPACT SIMULATOR FOR AUTOMOTIVE TRANSIENTS



FOR TESTS ACCORDING TO ...

- › Audi - Prüfkatalog für Referenzfahrzeuge
- › BMW - Erprobungshandbuch für Airbag-Steuerungen
- › BMW 600 13.0 (Part 2)
- › BMW GS 95002 (1999)
- › BMW GS 95002 (2001)
- › Chrysler DC-11224 Rev.A
- › Chrysler PF 9326
- › Cummins 14269 (982022-026)
- › DaimlerChrysler DC-10614
- › DaimlerChrysler PF-10540
- › EN 300329
- › EN 300340
- › EN 300342-1
- › EN 301489-1
- › EN 301489-17
- › EN 301489-24
- › EN 301489-7
- › FAW Diesel ECU MY06.0 (Rev.7)
- › Fiat 9.90110
- › Ford ES-XW7T-1A278-AB
- › Ford ES-XW7T-1A278-AC
- › Ford WDR 00.00EA
- › ...

ULTRA-COMPACT SIMULATOR FOR AUTOMOTIVE TRANSIENTS FOR PULSES 1, 2 AND 3A/3B

The UCS 200N Ultra-Compact Simulator for Automotive Transients unifies the capabilities of an EFT/Burst simulator, a Micropulse simulator and the required coupling network into one box. The UCS 200N is equipped to meet all international and car manufacturer specifications from around the globe. The built-in coupling network ranges up to 200A depending on the model. The built-in coupling network can be used and controlled by any unit of the LD 200N series, VDS 200N series and PFS 200N series.

For tests beyond standard's requirements the waveform parameters of the Micropulse generator can be varied in a wide range by means of the FreeStyle mode.

HIGHLIGHTS

- › **BUILT-IN EFT/BURST GENERATOR MODULE**
- › **BUILT-IN MICROPULSE GENERATOR MODULE INCL. JASO, SAE AND NISSAN**
- › **BUILT-IN COUPLING NETWORK 60V, UP TO 200A**
- › **CONTROLS EXTERNAL LOAD DUMP AND BATTERY SUPPLY SIMULATORS**
- › **USB AND GPIB-BUS**

APPLICATION AREAS

-  AUTOMOTIVE
-  TELECOM

TECHNICAL DETAILS

BENEFITS

SMARTEST SOLUTION FOR AUTOMOTIVE TRANSIENT TESTING

Never before an Ultra-Compact Simulator for automotive transient testing like the UCS 200N was available. All international standards and most car manufacturer requirements have been put into one box. All pulses are fully compliant to the specifications. Even more, the waveform parameters for micropulses can be varied in order to test with pulses beyond any standard specification.

The UCS 200N is the heart of the redesigned EM TEST Automotive test set-up having the ability to control any external EM TEST Load Dump and Battery Supply simulator. The built-in coupling network for nominal DC currents of up to 200A forms the single-port DUT connection for fully automated tests.

The software iso.control with its extensive standards library put this test equipment to the top with almost unlimited test capabilities.

OPERATION

EASY TO OPERATE

Front panel menu and function keys enable the user to program his test routines quickly and accurately. The cursor allows fast control of all test parameters of the programmed routine, thus test procedures are simplified and confidence is generated that every step is carried out correctly.

SOFTWARE

ISO.CONTROL SOFTWARE FOR CONTROL AND DOCUMENTATION

Outstanding user convenience, clearly structured windows and operation features and the EM TEST standards library along with the flexibility to generate user specific test sequences very easily are the main features of iso.control software. The software is automatically configured according to the connected EM TEST generators. iso.control software covers international/national standards and most of the manufacturer standards and is continuously updated. Extensive reporting capabilities help the user to create test reports that meet international requirements. iso.control is supported by Windows 2000, Windows XP and Windows Vista. Remote control is achieved either via USB or GPIB. iso.control supports a wide range of GPIB cards of National Instruments.

ACCESSORIES

ACC - CAPACITIVE COUPLING CLAMP

All lines other than supply lines are subjected to electrical fast transient pulses by means of the ACC complying to ISO 7637-3:2007

CA EFT KIT - VERIFICATION KIT FOR EFT/BURST PULSES

As per ISO 7637-2:2004 the characteristic of the burst generator needs to be verified with two different loads 50 ohm and 1,000 ohm. EM TEST offers a calibration kit consisting of the two loads and an adapter to verify the pulses.

CA ISO - LOAD RESISTORS FOR PULSE VERIFICATION

A set of highly-accurate load resistors is unified in a single box for the verification of micropulses and Load Dump pulses as specified in ISO 7637-2:2004, Annex D and a wide range of manufacturer specifications.

TECHNICAL DETAILS
ELECTRICAL FAST TRANSIENTS
EFT/BURST MODULE FOR TEST PULSES 3A/3B

	As per ISO 7637-2:2004
Test voltage	25V - 1,000V ± 10%
Rise time	5ns ± 1.5ns
Pulse duration	100ns (+100/-0)ns
Verification	As per Annex D of ISO 7637-2:2004 into 50ohm and 1,000ohm load
Source impedance	Z _q = 50ohm
Polarity	Positive/negative (Pulse 3b/3a)

TRIGGER CIRCUIT

Trigger of bursts	Automatic, manual, external
Burst duration	T ₄ = 0.1ms - 999.9ms
Repetition rate	T ₅ = 10ms - 9,999ms
Spike frequency	f = 0.1kHz - 200kHz
Test duration	T = 0:01min - 999:59min T > 999:59min --> endless

OUTPUTS

Direct	Via 50ohm-coaxial connector (for tests using e.g. a capacitive coupling clamp)
Coupling mode	To the + battery line (supply lines)
CRO trigger	5V trigger signal for oscilloscope

TEST ROUTINES

Quick Start	On-line adjustable parameters, easy-to-use
Standard Test routines	As per ISO 7637-2:2004, Levels 1 - 4 routines
User Test routines	Random burst release Change voltage after T Change frequency after T

OPTIONS

ACC	Capacitive coupling clamp
KW50	100:1 divider, 50ohm
KW1000	400:1 divider, 1,000ohm
CA EFT kit	EFT/Burst verification kit
A6dB	6dB attenuator, 50ohm

BUILT-IN COUPLING NETWORKS
TECHNICAL DATA FOR STANDARD CNA 50

DUT voltage	Max. 60V
DUT current	50A
Peak current	100A for 500ms
Dimensions	19"/3HU (UCS 200N incl. CNA 50)

TECHNICAL DATA FOR OPTIONAL CNA 100

DUT voltage	Max. 60V
DUT current	100A
Peak current	150A for 500ms
Dimensions	19"/6HU (UCS 200N incl. CNA 100)

TECHNICAL DATA FOR OPTIONAL CNA 150

DUT voltage	Max. 60V
DUT current	150A
Peak current	> 150A
Dimensions	19"/9HU (UCS 200N incl. CNA 150)

TECHNICAL DATA FOR OPTIONAL CNA 200

DUT voltage	Max. 60V
DUT current	200A
Peak current	> 200A
Dimensions	19"/9HU (UCS 200N incl. CNA 200)

INPUT

DUT supply +/-	From VDS 200N or PFS 200N
Pulse 5, 7	From one LD 200x

OUTPUT

DUT supply +/-	Central DUT output
Coaxial output port	To connect the capacitive coupling clamp as per ISO 7637-3:2007

TECHNICAL DETAILS

MICROPULSES

MICROPULSE MODULE FOR TEST PULSES 1, 2A AND 6

	As per ISO 7637-2:2004
Test voltage	U = 20V - 600V ± 10% (peak voltage and polarity as per selected standard)
Repetition rate	0.2s - 99.0s

ISO PULSE 1 (12V)

Rise time	1us +0%/-50% (10% - 90%)
Pulse duration	2ms ± 10% (10% - 10%)
Int. resistor	10ohm ± 10%

ISO PULSE 1 (24V)

Rise time	3us +0%/-50% (10% - 90%)
Pulse duration	1ms ± 10% (10% - 10%)
Int. resistor	50ohm ± 10%

ISO PULSE 2 (12V/24V)

Rise time	1us +0%/-50% (10% - 90%)
Pulse duration	50us ± 10% (10% - 10%)
Int. resistor	2ohm ± 10%

ISO PULSE 6 (12V)

Rise time	30us +0%/-50% (10% - 90%)
Pulse duration	600us ± 10% (10% - 10%)
Int. resistor	30ohm ± 10%

AS PER ISO 7637-2 THE FOLLOWING STANDARDS CAN BE COVERED

SAE J1113	GM 3097
BMW	Volkswagen
PSA	Chrysler PF 9326
DC 10614	Renault
FIAT	Mitsubishi
Honda	Ford ES-XW7T

FREESTYLE MODE MICROPULSES

PULSE PROGRAMMING MODE

Rise time	1us - 10us in steps of 1us
Pulse duration	50us - 10,000us
Int. resistor	2ohm - 100ohm in steps of 5ohm; 200ohm, 400ohm and 450ohm

TRIGGER

Automatic	Automatic release of the pulses
Manual	Manual release of a single pulse
External	External release of a single pulse
Supply switch	Off time, selectable; 0 - 10,000ms

OUTPUT

DUT supply +/-	Central DUT output
Coupling	To the battery +line
Decoupling	Via diode and battery supply switch

TEST ROUTINES

Quick Start	Immediate start; easy to use and fast
User Test routines	1. Custom made test routines 2. Change voltage after n pulses
Standard Test routines	As per ISO 7637, SAE J1113, JASO and manufacturer specifications
Service	Service, setup, self test

TECHNICAL DETAILS

MICROPULSES AS PER MANUFACTURER STANDARDS

JASO D-001, PULSE A2

Test voltage	+110V
Capacitor	C = 4.7uF
Pulse duration	2.5us ± 30% at tau(36.8%)
R1	0.6ohm ± 10%
R2	0.4ohm ± 10%
Polarity	Positive

JASO D-001, PULSE B2

Test voltage	-260V
Capacitor	C = 33uF
Pulse duration	2.0ms ± 20% at tau(36,8%)
R1	60ohm ± 10%
R2	80ohm ± 10%
Polarity	Negative

JASO D-001, PULSE D2

Test voltage	+170V
Capacitor	C = 2.2uF
Pulse duration	2.5us ± 30% at tau(36,8%)
R1	1.2ohm ± 10%
R2	0.9ohm ± 10%
Polarity	Positive

NISSAN 28400 NDS 03, PULSE B2

Test voltage	-300V ± 10%
Capacitor	C = 33uF
R1	100ohm ± 10%
R2	75ohm ± 10%
Polarity	Negative

NISSAN 28400 NDS 07, PULSE C8

Test voltage	±300V ± 10%
Capacitor	C = 1uF
R1	500ohm ± 10%
R2	450ohm ± 10%
Polarity	Positive and negative

NISSAN 28400 NDS 07, PULSE C50

Test voltage	±300V ± 10%
Capacitor	C = 33uF
R1	30ohm ± 10%
R2	200ohm ± 10%
Polarity	Positive and negative

NISSAN 28400 NDS 07, PULSE C300

Test voltage	-300V ± 10%
Capacitor	C = 33uF
R1	100ohm ± 10%
R2	75ohm ± 10%
Polarity	Negative

SAE J1455 | MUTUAL PULSE

Rise time	1us ± 20% (10% - 90%)
Pulse duration	15µs ± 20% at tau(36.8%)
Int. resistor	50ohm ± 10%

SAE J1455 | INDUCTIVE PULSE

Rise time	1us ± 20% (10 - 90%)
Pulse duration	1,000us ± 20% at tau(36.8%)
Int. resistor	20ohm ± 10%

OPTIONS

CA ISO	Load resistors for the verification of micropulses and Load Dump pulses
--------	---

TECHNICAL DETAILS

GENERAL DATA

DIMENSIONS AND WEIGHT

UCS 200N	19"/3HU, approx. 20kg
UCS 200N with CNA100	19"/6HU, approx. 30kg
UCS 200N with CNA150	19"/9HU, approx. 35kg
UCS 200N with CNA200	19"/9HU, approx. 35kg
Supply voltage	115/230V +10/-15%
Fuses	2 x T 2AT (230V) or 2 x T 4AT (115V)


INTERFACE

Serial interface	USB
Parallel interface	IEEE 488, address 1 - 30
CN interface	To control the internal CN and battery switch

OPTIONS

CNA/Ext	Extention to connect up to three additional pulse generators.
iso.control	Software to control the test, including standard library, test report facility and data conversion generator.
Rack	For system integration; includes GPIB bus, pulse bus, ground reference plane, security switch and power contact.

COMPETENCE WHEREVER YOU ARE



CONTACT EM TEST DIRECTLY

Switzerland

EM TEST AG › Sternenhofstraße 15 › 4153 Reinach › Switzerland
Phone +41 (0)61/7179191 › Fax +41 (0)61/7179199
Internet: www.emtest.ch › E-mail: sales@emtest.ch

Germany

EM TEST GmbH › Lünener Straße 211 › 59174 Kamen › Deutschland
Phone +49 (0)2307/26070-0 › Fax +49 (0)2307/17050
Internet: www.emtest.com › E-mail: info@emtest.de

France

EM TEST FRANCE › Le Trident - Parc des Collines › Immeuble B1 - Etage 3 ›
36, rue Paul Cézanne › 68200 Mulhouse › France
Phone +33 (0)389 31 23 50 › Fax +33 (0)389 31 23 55
Internet: www.emtest.fr › E-mail: info@emtest.fr

P.R. China

EM TEST Representative Office Beijing › Rm 913, Leftbank ›
No. 68 Bei Si Huan Xi Lu › Haidian District › Beijing 100080 › P.R. China
Phone +86 (0)10 82 67 60 27 › Fax +86 (0)10 82 67 62 38
Internet: www.emtest.com › E-mail: emtestbj@public.bta.net.cn

Malaysia

EM TEST (M) SDN BHD › Unit B2-6, Jalan Dataran SD2 › Dataran SD2, PJU9 ›
Bandar Sri Damansara › 52200 Kuala Lumpur › Malaysia
Phone +60 (03)62 73 22 01 › Fax +60 (03)62 74 22 01
Internet: www.emtest.com › E-mail: sales@emtest.com.my

Poland

EM TEST Polska › ul. Lema 33, 26-613 Radom › Polska
Phone +48 518 64 35 12 › E-mail: info.polska@emtest.de

Information about scope of delivery, visual design and technical data correspond with the state of development at time of release.
Technical data subject to change without further notice.