



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4044
2 - 30 MHz
2000 WATTS
LINEAR POWER RF AMPLIFIER

Solid State Band-Specific High Power RF Amplifier

The 4044 is a 2000 Watt band-specific amplifier that covers the 2 – 30 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4044 comes with an extended multiyear warranty.



FE Model Shown

	Parameter	Specification @ 25° C
<u>Electrical</u>		
1	Frequency Range	2 – 30 MHz
2	Saturated Output Power	2000 Watts typical
3	Power Output @ 1dB Comp.	1200 Watts min
4	Small Signal Gain	+63 dB min
5	Small Signal Gain Flatness	± 2.0 dB max
6	IP ₃	+67 dBm
7	Input VSWR	2:1 max
8	Harmonics	-15 dBc typical @ 1200 Watts
9	Spurious Signals	-60 dBc typical @ 1200 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	5500 Watts max
12	AC Input	208 ± 10% VAC, single phase
13	Nominal RF Input	0 dBm
14	RF Input Overdrive	+13 dBm max
15	RF Input Signal Format	CW/AM/FM/PM
16	Class of Operation	AB
<u>Mechanical</u>		
17	Dimensions* (W x H x D)	22.5" x 31" x 26"
18	Weight*	300 lbs. max
19	RF Connectors	Type-N
20	Grounding	Chassis
21	Cooling	Internal Forced Air
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

* Dimensions and weight include cabinet enclosure.

Specifications subject to change without notice.

CIRCUIT PROTECTIONS

- ◇ Thermal Shutdown
- ◇ Over Voltage
- ◇ High VSWR Alarm
- ◇ RF Input Overdrive Protection

ORDERING MODELS

- ◇ RE - Rear panel RF connectors with control Option
- ◇ FE - Front panel RF connectors with control option
- ◇ RT - RE model with Ethernet connectivity interface
- ◇ FT - FE model with Ethernet connectivity interface