



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9887
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4046-002
1270 - 1310 MHz
300 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Band-specific High
 Power RF Amplifier**

The 4046-002 is a 300 Watt band-specific amplifier that covers the 1270 – 1310 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4046-002 comes with an extended multiyear warranty.

	Parameter	Specification @ 25 °C
Electrical		
1	Frequency Range	1215 – 1450 MHz
2	Saturated Output Power	300 Watts typical
3	Power Output @ 1dB Comp.	240 Watts min
4	Small Signal Gain	+56 dB min
5	Small Signal Gain Flatness	± 1.5 dB max
6	IP ₃	+63 dBm typical
7	Input/Output VSWR	2:1 max
8	Harmonics	-20 dBc typical @ 240 Watts
9	Spurious Signals	> -60 dBc typical @ 240 Watts
10	Input/Output Impedance	50 Ohms nominal
11	AC Input Power	2000 Watts max
12	AC Input	100 – 240 VAC, single phase
13	RF Input	10 dBm max.
14	RF Input Signal Format	CW/AM/FM/PM/Pulse
15	Class of Operation	AB
Mechanical		
16	Dimensions	19" x 8.75" x 24"
17	Weight	100 lb. max
18	Connectors	Type-N
19	Grounding	Chassis
20	Cooling	Internal Forced Air
Environmental		
21	Operating Temperature	0° C to +50° C
22	Operating Humidity	95% Non-condensing
23	Operating Altitude	Up to 10,000' Above Sea Level
24	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice.

CIRCUIT PROTECTIONS

- ◇ Infinite Load VSWR with isolator
- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

