



5300 Beethoven Street, Los Angeles, CA 90066
TEL: (310)306-5556 • FAX: (310)577-9779
WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 4060
1.85 - 2.17 GHz
120 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
Band-specific High
Power RF Amplifier**

The 4060 is a 120 Watt band-specific amplifier that covers the 1.85-2.17 GHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 4060 comes with an extended multiyear warranty.

CIRCUIT PROTECTIONS

- ◇ Infinite Load VSWR
- ◇ RF Input Overdrive
- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

AVAILABLE OPTIONS

- ◇ LCD Digital Display
- ◇ IEEE-488 GPIB
- ◇ Gain Adjustment
- ◇ Automatic Level Control
- ◇ Extended Temperature Range
- ◇ Rear Panel Connectors
- ◇ Rack Mounting Slide
- ◇ Different Case Styles

	<u>Parameter</u>	<u>Specification</u>
<u>Electrical</u>		
1	Frequency Range	1.85 – 2.17 GHz
2	Saturated Output Power	120 Watts typical
3	Power Output @ 1dB Comp.	100 Watts min
4	Power Output @ CDMA	25 Watts typical
5	Small Signal Gain	+53 dB min
6	Small Signal Gain Flatness	± 0.75 dB max
7	IP ₃	+61 dBm typical
8	Input VSWR	2:1 max
9	Harmonics	-20 dBc typical @ 1 dB comp.
10	Spurious Signals	> -60 dBc
11	Input/Output Impedance	50 Ohms nominal
12	AC Input Power	500 Watts max
13	AC Input	100 – 240 VAC, single phase
14	RF Input Overdrive	+10 dB over 1 dB Compression
15	RF Input Signal Format	CW/AM/FM/PM/Pulse
16	Class of Operation	A/AB Linear
<u>Mechanical</u>		
17	Dimensions	19" x 7" x 20"
18	Weight	47 lb. max
19	Connectors	Type-N
20	Grounding	Chassis
21	Cooling	Internal Forced Air
<u>Environmental</u>		
22	Operating Temperature	0° C to +50° C
23	Operating Humidity	95% Non-condensing
24	Operating Altitude	Up to 10,000' Above Sea Level
25	Shock and Vibration	Normal Truck Transport

