



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)577-9779
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5303060
1 - 1000 MHz
4 WATTS
LINEAR POWER RF AMPLIFIER

**Solid State
 Broadband High
 Power RF Amplifier**

The 5303060 is a 4 Watt broadband amplifier that covers the 1 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5303060 comes with an extended multiyear warranty.

| | <u>Parameter</u> | <u>Specification</u> |
|-----------------------------|--------------------------|-------------------------------|
| <u>Electrical</u> | | |
| 1 | Frequency Range | 1 – 1000 MHz |
| 2 | Saturated Output Power | 4 Watts typical |
| 3 | Power Output @ 1dB Comp. | 2 Watts min |
| 4 | Small Signal Gain | +36 dB min |
| 5 | Gain Flatness | ± 1.5 dB max |
| 6 | IP ₃ | +43 dBm typical |
| 7 | Input VSWR | 2:1 max |
| 8 | Harmonics | -20 dBc typical @ 1 dB comp. |
| 9 | Spurious Signals | > -60 dBc |
| 10 | Input/Output Impedance | 50 Ohms nominal |
| 11 | DC Input Current @ 200W | 1.2 Amps max |
| 12 | DC Input | 24 – 30 VDC nominal |
| 13 | RF Input Overdrive | +10 dB over 1 dB Compression |
| 14 | RF Input Signal Format | CW/AM/FM/PM/Pulse |
| 15 | Class of Operation | A/AB Linear |
| <u>Mechanical</u> | | |
| 16 | Dimensions | 6" x 3" x 1.1" |
| 17 | Weight | 2 lb. max |
| 18 | Connectors | SMA female |
| 19 | Grounding | Chassis |
| 20 | Cooling | Adequate Heatsink Required |
| <u>Environmental</u> | | |
| 21 | Operating Temperature | 0° C to +50° C |
| 22 | Operating Humidity | 95% Non-condensing |
| 23 | Operating Altitude | Up to 10,000' Above Sea Level |
| 24 | Shock and Vibration | Normal Truck Transport |

AVAILABLE OPTIONS

- ◇ Gain Adjustment
- ◇ Automatic Level Control
- ◇ Extended Temperature Range
- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

