

STEUSB3AA Universal USB I/O Connector



UNIVERSAL USB... MAXIMUM SHIELDING!



- ✓ Dual Type-A receptacles
- ✓ Designed to pass all USB standards including USB3.1Gen2, USB3.1Gen1, USB3.0, USB2.0, USB1.1
- ✓ Data speeds up to 10Gbit/s at Superspeed+
- ✓ Simple single-hole mount and rugged milled and plated aluminum construction with RF gasket
- ✓ Includes screw-on captive port shield bonding cover for maximum shielding

THE ULTIMATE PASSIVE UNIVERSAL USB CONNECTOR!

The Ramsey Electronics® STEUSB3AA provides a 100% shielded USB type A to A connector solution for your RF Shielded Test Enclosure. Shielding and bonding to the enclosure is maintained with its single-hole RF gasketed mounting configuration. The USB interface connector is designed to be installed on the I/O panel of your test enclosure but can also be installed on any RF enclosure wall up to .112".

USB3.1 SERIES DATA TRANSFERS UP TO 10Gbit/s

Now there is no reason to have separate USB2.0 and USB3.x connectors reducing your I/O costs, I/O space requirements, and I/O redundancy. The feedthrough connector is designed to pass all USB data and encoding schemes:

- ✓ USB3.1 Gen2 Superspeed+ 10Gbit/s
- ✓ USB3.1 Gen1 Superspeed 5Gbit/s
- ✓ USB3.0 Superspeed 5Gbit/s
- ✓ USB2.0 Highspeed 480Mbit/s
- ✓ USB1.1 Fullspeed 12Mbit/s

While the STEUSB3AA bulkhead interface connector is not RF filtered and does not provide any conductive RF isolation, it does provide a 100% shielded solution that is transparent to, and fully compatible with the USB configurations above. Like any unfiltered I/O interfaces, strict shielding practices need to be maintained throughout your connections to minimize chamber RF ingress and egress. RF filtered interfaces are recommended wherever possible, and the use of this or any other unfiltered connectors in your specific RF shielded environment should be verified by your engineering department prior to ordering.

CAPTIVE SHIELDED PORT COVER

Unlike other USB bulkhead data connectors, when not in use, the data port can be capped off with the included captive shielded bonding cover, shielding the exposed data connector from the ambient free-air RF signals outside of the enclosure. Like all of our other connector shield caps, the cover is tethered and bonded to the RF Test Enclosure case ground.

THE RF ISOLATION LEADER!

With thousands of RF Shielded Test Enclosures placed in service worldwide, our RF isolation technologies have become the global standard not only for RF isolated chambers, but for the best matching I/O interfaces available.

From 10GbE Ethernet to 4K HDMI interconnectivity while maintaining >85 dB RF isolation! Check out our full line of isolated interfaces at www.ramseytest.com.

SPECIFICATIONS	
Product Part Number:	STEUSB3AA
UPC	871183006208
Outside Dimensions:	.87"H x .87"W x 1.36"D (22.17mmH x 22.17mmW x 34.54mmD)
Weight:	1.6oz (.04kg) with nut, and RF gasket
Construction:	Nickel plated aluminum
Mounting:	Single 1" OD D-hole with provided EMI collar gasket, and 7/8-20 UNEF jam nut (.112"/2.85mm max panel thickness)
Body Style:	MIL-DTL-38999
External Connection:	USB3.x Type-A receptacle
Internal Connection:	USB3.x Type-A receptacle
Data Rating:	Up to 10Gbit/s for USB3.1Gen2 Superspeed+
Current Rating:	Pins 1&4 1.8A, other pins .25A
Temperature Rating:	-20°C to +85°C
Shielded Cover:	Screw-on with bonded and captive lanyard

Note: Specifications are average achieved and certified final test measurement values. Subject to change and revisions. Not responsible for typographical errors and omissions.



RAMSEY ELECTRONICS®
590 Fishers Station Drive, Victor NY USA (585) 924-4560