

Data Sheet

HLP-2603 Hybrid Log Periodic Antenna

Product Overview

Ultra Wide Range The TDK HLP-2603 Hybrid Log Periodic antenna offers unequaled performance over the ultra wide frequency range of 26 MHz to 3 GHz for EMC immunity measurements. Significant time savings can be realized while testing to the various European, North American, and Asian standards because you are able to test continuously across the frequency range of interest. The HLP-2603 is designed for testing at 10 V/m with 80% AM modulation with minimum amplifier requirements.

Features

- High gain
- Low VSWR
- Ultra broadband
- High capacity power input
- Quality construction
- Provides significantly improved performance over competing designs

Applications

Radiated immunity testing



The TDK HLP-2603 Hybrid LPD antenna offers unequaled performance over the ultra wide frequency range of 26 MHz to 3 GHz.

Options

Manual Vertical Mast MVM-200R
The TDK MVM-200R antenna mast provides manual control of the height, tilt, and polarization. The MVM-200R adjusts from 1 m to 1.5 m in height and supports antennas up to 18 kg.



HLP-2603 Hybrid Log Periodic Antenna

Electrical Specifications

Gain:

Frequency Range: 26 MHz to 3 GHz

VSWR: <2:1 average

Polarization: Linear

Power Handling 1.0 kW maximum
Feedpoint Impedance 50 ohms (nominal)

Mechanical Specifications

Size: $1.5 \text{ m} \times 1.5 \text{ m} \times 0.74 \text{ m}$

(60" W x 60" D x 29"

6 to 8 dBi typical

H)

Weight: < 8.5 kg

Construction: Aluminum with gold

chromate finish

RF Connector: 7/16 female

Ordering Information

Product: Hybrid Periodic Log

Antenna

Model Number: HLP-2603

Warranty: 1 year limited

To place an order or to learn more about the TDK products that best meet your needs, contact your TDK sales representative:

TDK RF Solutions Inc.

1101 Cypress Creek Rd. Cedar Park, Texas 78613 USA

Phone: 1-512-258-9478
Fax: 1-512-258-0740
E-mail: info@tdkrf.com

World Wide Web: <u>www.tdkrfsolutions.com</u>

Environmental Specifications

Ambient Temperature Limits:

Operating: 0° to +40° C

Storage: -10° to +50° C

Humidity: Up to 95% non-

condensing



www.tdkrfsolutions.com