



AMP2012A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Small form factor rack-mounted system
- Class AB linear LDMOS design
- Instantaneous RF & VHF bands wide bandwidth coverage
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

| Parameter | Specification | Notes |
|------------------------------|----------------|-------------------------|
| Operating Frequency Range | 2 - 100 MHz | |
| Power Output | 500 Watt Min | CW |
| Power Gain | 57 dB Min | |
| Power Gain Flatness | 3.0 dB p-p Max | |
| Input Return Loss | -10 dB Max | Relative to 50 Ohm |
| 2-Tone Intermodulation (IMD) | -30 dBc Typ | 47dBm/Tone, Δ = 1MHz |
| Harmonics | -20 dBc Typ | |
| Spurious | -60 dBc Max | Non-harmonics |
| Operating Voltage | 100 - 240 VAC | |
| Power Consumption | 2000 Watt Max | At rated Pout |
| Input Power Protection | +8 dBm Max | <10 Sec without damage |
| Load VSWR Protection | ∞ : 1 | <1 minute at rated Pout |

ENVIRONMENTAL CHARACTERISTICS

| Parameter | Specification | Notes |
|-------------------------------|---------------|----------------|
| Operating Ambient Temperature | 0 to +50 °C | |
| Storage Temperature | -40 to +85 °C | |
| Relative Humidity | 5 to 95 % | Non-condensing |

MECHANICAL SPECIFICATIONS

| Parameter | Specification | Notes |
|--|--|------------------------------|
| Dimensions W x H x D | 430 x 133 x 560 mm | 3U |
| Weight | 25 Kg. Max | |
| RF Connectors In/Out | Type-N Female | Front or rear panel |
| AC Power | IEC 60320-C14 / 9-Pin D-Sub | Or equivalent |
| Cooling | Built in Fan Cooling | Variable speed |
| OPTION: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP | Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface | Remote Bluetooth application |

AMP2012A SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

