



AMP2021A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class AB linear GaN design
- Instantaneous ultra-wide bandwidth
- Designed for broadband EMI/RFI, Lab, Comm. and EW applications
- Suitable for all single channel modulation standards
- Rack mounted system
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	500 - 2500 MHz	
Power Output	100 Watt Min	CW
Power Gain	50 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Gain Adjustment Range	20 dB Min	
Input / Output Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	40dBm/Tone, $\Delta = 1$ MHz
Harmonics	-20 dBc Typ	At rated output power
Spurious	-60dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	400 Watt	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	$\infty : 1$	<1 minute at rated Pout
Sample Port Coupling	-30 to -40 dB	Optional - SMA F

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing
Shock & Vibration	MIL-STD-810E	Designed to meet

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 88 x 560 mm	2U - Excluding handles
Weight	10 kg.	
RF Connectors In / Out / Sample Port	Type-N Female / SMA-F	Rear or Front panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	

AMP2021A SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

