



# AMP2025-1 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Rack mounted system
- Class AB linear GaN design
- Instantaneous wide bandwidth
- Suitable for all single channel modulation standards
- Local LCD & remote flexible interfaces
- Designed for EMI/RFI, lab, and general communication applications
- High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	1.0 - 2.5 GHz	
Power Output	250 Watt Min	CW
Power Gain	54 dB Min	
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation	<-30 dBc Typ	45dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	<-20 dBc Typ	At rated output power
Spurious	60dBc Min	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	1400 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	10 Sec without damage
Load VSWR Protection	5 : 1	<1 minute at rated Out

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U
Weight	20 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
<b>EMI SERIES:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Remote Bluetooth application

## OUTLINE DRAWING

