

AMP2026B SOLID STATE HIGH POWER AMPLIFIER



FEATURES

Rack mounted system
 Class AB linear GaN design
 Instantaneous wide bandwidth
 Suitable for all single channel modulation standards
 Built-in protection circuits
 High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	2.0 - 6.0 GHz	
Power Output @ Psat	500 Watt Min	CW
Power Gain	57 dB Min	
Power Gain Flatness	4 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	47dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	-20 dBc Typ	At rated output
Spurious	-60 dBc Max	Non-harmonic
Operating Voltage	180 - 240 VAC	
Power Consumption	4 KW Max	At rated output
Max Input Power Protection	+8 dBm	Note 1
Load VSWR Protection	5 : 1	Note 2

Notes:

- Nominal Input Power is 0dBm. +8dBm is allowed for up to 10Sec with no damage.
- 1 Minute Max @ rated min Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 311 x 600 mm	R7U Rack Mount Chassis
Weight	45 Kg. Max	
RF Connectors In/Out	Type-N Female	Front Panel Standard
AC Power	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Remote Bluetooth application

OUTLINE DRAWING

