



# AMP2053-1 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Rack mounted system
- Class AB Solid-State linear Hybrid design
- Instantaneous wide bandwidth
- Suitable for all single channel modulations standards
- Built-in protection circuits
- High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	6.0 - 10.0 GHz	
Power Output	50 Watt Min	CW
Power Gain	47 dB Min	
Power Gain Flatness	3 dB p-p Max	Constant input power
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Min	37dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	>25 dBc Typ	At rated output power
Non Harmonics Spurious	60 dBc Min	
Operating Voltage	100 - 240 VAC	
Power Consumption	400 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	5 : 1	

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 560 x 133 mm	3U - Without handles
Weight	20 kg.	
RF Connectors In / Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485	Remote Bluetooth application

# AMP2053-1 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

