



AMP2068 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class A/AB linear GaN design
- Rack mounted system
- Instantaneous wide bandwidth
- Suitable for broadband EMI/RFI, Lab, Comm., and EW applications
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness for mobile applications



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	0.8 - 2.5 GHz	
Power Output @ Saturation	500 Watt Min	CW
Power Output @ P1dB	200 Watt Min	
Power Gain	57 dB Min	Pin=0dBm for normal operation
Power Gain Flatness	3.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	<-30 dBc Typ	47dBm/Tone, Δ = 1MHz
Harmonics	<-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	180 - 240 VAC	
Power Consumption	3 KW Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 222 x 560 mm	5U - Excluding handles
Weight	35 Kg	
RF Connectors In / Out	Type-N Female	Front or rear panel
AC Power / Interface	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control: FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Optional Remote Bluetooth application

AMP2068 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

