



AMP2071-1 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Class AB linear LDMOS design
- Instantaneous wide bandwidth
- Suitable for AM, FM, Pulse and other modulations standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	220 - 1000 MHz	
Power Output @ Saturation	500 Watt Min	CW
Power Output @ P1dB Gain Compression	400 Watt Typ	
Power Gain	57 dB Min	Pin=0dBm for nominal Pout
Power Gain Flatness	3.0 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD / IP3)	-30 dBc Min	47dBm/Tone, Δ = 1MHz
Noise Figure	8 dB Max	
Harmonics	>20 dBc	
Non Harmonic Spurious	>60 dBc	
Operating Voltage	180 - 240 VAC Single Phase	50/60Hz
Power Consumption	2500 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	6 : 1 Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 222 x 560 mm	5U rack mount
Weight	40 Kg. Max	
RF Connectors In/Out	Type-N Female	
AC Power / Monitoring Connectors	IEC 60320-C14 / 9 Pin D-Sub	Or equivalent
Safety Interlock Connector	15-Pin Subminiature D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS-232 USB 2.0, GPIB/IEEE Interface	Remote Bluetooth application

AMP2071-1 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

