

# AMP2071 SOLID STATE HIGH POWER AMPLIFIER



## FEATURES

- Rack mounted system
- Class AB linear LDMOS design
- Instantaneous ultra-wide bandwidth
- Designed for broadband EMI/RFI, Lab, Comm. and EW applications
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness

## ELECTRICAL SPECIFICATIONS: 25°C, 50Ω

Parameter	Specification	Notes
Operating Frequency Range	80 - 1000 MHz	
Power Output @ Saturation	500 Watt Min	CW
Power Output @ P1dB GCP	400 Watt Typ	
Power Gain	57 dB Min	Pin=0dBm for nominal Pout
Power Gain Flatness	3.0 dB p-p Max	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Min	47dBm/Tone, Δ = 1MHz
Noise Figure	8 dB Max	
Harmonics	-20 dBc Max	
Spurious	-60 dBc Max	Non-harmonic
Operating Voltage	180 - 240 VAC Single Phase	50/60Hz
Power Consumption	2500 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection (Note 1)	6 : 1 Max	<1 minute at rated Pout

1. Auto shutdown with controller option

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 221 x 560 mm	5U - Excluding handles
Weight	40 Kg. Max	
RF Connectors In/Out	Type-N Female	Front or rear panel
AC Power / Monitoring Connectors / Interlock	IEC 60320-C14 / 9 Pin D-Sub	Or equivalent
Cooling: Built in Fan Cooling	72 dBa Typ	Variable speed
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS-232, USB Optional GPIB/IEEE Interface	Optional Remote Bluetooth application

# AMP2071 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

