



AMP2107ADB SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Class AB linear GaN design
- Dual-Band, manual relay switching
- Designed for broadband EMI/RFI, Lab, Communication applications
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification		Notes
	Band A	Band B	
Band			
Operating Frequency Range by Band	0.5 - 6 GHz	6 - 18 GHz	
Power Output @ Psat	50 Watt Min		CW
Power Gain	47 dB Min		
Power Gain Flatness	4.0 dB p-p Max	6.0 dB p-p Max	Constant input power
Input Return Loss	-10 dB Max		Relative to 50 Ohm
2-Tone Intermodulation (IMD) Band A / Band B	-30 dBc Typ		37dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ Note: -13 dBc to -15 dBc @ 500 MHz		At rated Pout
Spurious	-60 dBc Max		Non-harmonics
Operating Voltage	100 - 240 VAC		
Power Consumption	600 Watt Max		At rated Pout
Input Power Protection	+3 dBm Max		<10 Sec without damage
Load VSWR Protection	5 : 1 Max		<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U- Excluding handles
Weight	20 Kg. Max	
RF Connectors In/Out	Hi Freq. Type-N Female	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	

AMP2107ADB SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

