



AMP4021-1 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Class A/AB Solid-State linear GaN Hybrid design
 Rack mounted system
 Designed for high power X-Band instantaneous wide bandwidth
 Suitable for all single channel modulation standards
 Built-in protection circuits
 High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	7.0 - 10.0 GHz	
Power Output @ Psat	150 Watt Min / 200 Watt Typ	CW
Power Gain	53 dB Min	
Power Gain Flatness	3 dB p-p Max	Constant input power
Input / Output Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	42dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	<-30 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	1500 Watt Max	At rated Pout
Input Power Protection	+5 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS


Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 178 x 560 mm	4U - Without handles
Weight	30 kg. Max	
RF Connectors In / Out	Type N-F / WR112	Front or rear panel
AC Power / Interface Connector	MS / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Remote Bluetooth application

AMP4021-1 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



- *. NOTE
1. 4U, 4.3" LCD.
 2. RF IN/OUT Connector : N type Female
 3. AC Connector : IEC 60320-C14