

# AMP4023 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Rack mount system
- Class AB linear GaN design
- Instantaneous bandwidth
- Suitable for all modulations standards
- Built-in protection circuits
- Optional LCD-uP remote Control & Monitoring
- High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	2 - 3 GHz	
Power Output	50 Watt Min	CW
Power Gain	47 dB Min	
Power Gain Flatness	2.0 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	37dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	-20 dBc Typ	
Non Harmonics Spurious	-60 dBc Mx	
Operating Voltage	100 - 240 VAC	
Power Consumption	300 Watt Max	At Rated Pout
Max Input Power	+8 dBm	<10 Seconds without damage
Load VSWR Protection	$\infty : 1$	<1 Minute @ rated output

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 88 x 562 mm	2U
Weight	10 kg.	
RF Connectors In/Out	Type-N Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application

# AMP4023 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

