



## AMP4047 & AMP4047A SOLID STATE HIGH POWER AMPLIFIER

### FEATURES

- Small form factor Bench-Top chassis
- Class A/AB linear GaAsFET design
- Instantaneous wide bandwidth
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



### ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification		Notes
	AMP4047	AMP4047A	
Model	AMP4047	AMP4047A	
Operating Frequency Range	18 - 26.5 GHz	26 - 40 GHz	
Power Output CW	5 Watt Min		CW
Power Output @ P1dB	3Watt Typ		
Power Gain	37 dB Min		
Power Gain Flatness	4.0 dB p-p Max		Constant input power
Input Return Loss	-10 dB Max		Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ		27dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ		At rated Pout
Spurious	-60 dBc Max		Non-harmonics
Operating Voltage	100 - 240 VAC		
Power Consumption	120 Watt Max		At rated Pout
Input Power Protection	+3 dBm Max		<10 Sec without damage
Load VSWR Protection	5 : 1 Max		<1 minute at rated Pout

### ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

### MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	265 x 88 x 229 mm	2U Benchtop - wo handles
Weight	8 kg.	
RF Connectors In/Out	2.9 mm K- Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Only available in a 2U chassis

# AMP4047 & AMP4047A SOLID STATE HIGH POWER AMPLIFIER

## BENCH TOP CHASSIS

