

AMP4052 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Class AB linear GaAsFET design
- Instantaneous wide bandwidth
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	32 - 40 GHz	
Power Output CW	10 Watt Min	CW
Power Output @ P1dB	6 Watt Typ	
Power Gain	40 dB Min	
Power Gain Flatness	4.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	30dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	720 Watt Max	At rated Pout
Max Input Power	+3 dBm	<10 Seconds without damage
Load VSWR Protection	5 : 1	<1 Minute @ rated output

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 112 x 560 mm	2.5U
Weight	11 Kg. Target	
RF Connectors In/Out	2.9 mm (K / air type) Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS232/422/485	



AMP4052
SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING