



AMP4064A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Designed for X-Band linear applications
- Class AB Solid-State linear hybrid design
- Instantaneous wide bandwidth
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

| Parameter | Specification | Notes |
|------------------------------|--------------------------------|--|
| Operating Frequency Range | 7.9 - 8.5 GHz | |
| Power Output @ Psat | >150 Watt Typ | CW |
| Power Output @ P1dB GCP | 100 Watt Min | CW |
| Power Gain | 50 dB Min | Gain adjust |
| Power Gain Flatness | 2 dB p-p Max | Constant input power |
| Gain Adjustment Range | 20 dB Min | |
| Input / Output Return Loss | 10 dB Min | Relative to 50 Ohm |
| 2-Tone Intermodulation (IMD) | -30 dBc Typ | 40dBm/Tone, $\Delta = 1\text{MHz}$ |
| Harmonics | -30 dBc Min | At rated output power |
| Spurious | -60 dBc Max | Non-harmonics |
| Operating Voltage | 100 - 240 VAC | 40VDC option available |
| Power Consumption | < 800 Watt Typ / 1300 Watt Max | At rated Pout |
| Input Power Protection | +5 dBm Max | <10 Sec at without damage |
| Load VSWR Protection | 5 : 1 | Output isolator option available for Infinite VSWR at rated output |

ENVIRONMENTAL CHARACTERISTICS

| Parameter | Specification | Notes |
|-------------------------------|---------------|------------------|
| Operating Ambient Temperature | 0 to +50 °C | |
| Storage Temperature | -40 to +85 °C | |
| Relative Humidity | 5 to 95 % | Non-condensation |

MECHANICAL SPECIFICATIONS

| Parameter | Specification | Notes |
|--|--|------------------------------|
| Dimensions W x H x D | 483 x 178 x 640 mm (19" x 7" x 25") | 4U - Without handles |
| Weight | 30 Kg. | |
| RF Connectors In / Out | Type-N Female (or WG output) | Front panel |
| AC Power / Interface Connector | IEC 60320-C14 / 9-Pin D-Sub | |
| Cooling | Built in Fan Cooling | Variable speed |
| OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP | Ethernet RJ-45 TCP/IP, RS422/485 GPIO Interface | Remote Bluetooth application |

OUTLINE DRAWING

