



# AMP4072 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Class A/AB linear design
- Rack mounted system
- Instantaneous wide bandwidth
- Designed for EMI/RFI, lab, and general communication applications
- Suitable for all single channel modulation standards
- Local LCD & remote flexible interfaces
- High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS: 50Ω, 25°

Parameter	Specification	Notes
Operating Frequency Range	26.5 - 40.0 GHz	
Power Output	10 Watt Typ	Saturated CW
Power output at P1dB GCP	6 Watt Typ	
Power Gain	40 dB Min	
Power Gain Flatness	6.0 dB p-p Max	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
Noise Figure	12 dB Max	
Harmonics	-20 dBc Typ	At rated Pout
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	450 Watt Max	At rated Pout
Input Power Protection	+3 dBm Max	<10 Seconds without damage
Load VSWR Protection	∞ : 1	<1 Minute at rated Pout

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 88 x 562 mm	2U - Excluding connectors
Weight	10 kg.	
RF Connectors In/Out	2.9 mm (K / air type) Female	Front or rear panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	

# AMP4072 SOLID STATE HIGH POWER AMPLIFIER

**OUTLINE DRAWING - SHOWN WITH OPTIONAL LCD**

