



# AMP6001 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Rack mounted system
- Class AB linear GaN hybrid design
- Suitable for all modulations standards
- Built-in protection circuits
- High reliability and ruggedness

## ELECTRICAL SPECIFICATIONS



Parameter	Specification	Notes
Operating Frequency Range	14.615 ± 0.24 GHz	
Power Output @ P1dB GCP	50 Watt Min	CW
Power Gain	32 dB Min	
Power Gain Flatness	3.0 dB p-p Max	
Input Return Loss	15 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	37dBm/Tone, Δ = 1MHz
Harmonics	>30 dBc Typ	At rated Pout
Non Harmonics Spurious	60 dBc Min	Non Harmonics
Noise Figure	6.5 dB Max	
Operating Voltage	100 - 240 VAC	
Power Consumption	250 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	∞ : 1	

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 88 x 562 mm	2U
Weight	9 kg.	
RF Connectors In/Out	Type-N Female	Front Panel Standard
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application

# AMP6001 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

