



# AMP6032-1 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

- Ku-Band high power CW applications
- Rack mounted system
- Linear high power GaN design
- Built-in protection circuits
- High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	14.4 - 14.6 GHz	Nominal
Power Output @ Psat	150 Watt Min	CW
Power Gain	52 dB Min	
Input / Output Return Loss	10 dB Min	Relative to 50 Ohm
Harmonics	-30 dBc Max	At rated output
Non-Harmonic Spurious	-60 dBc Max	
Operating Voltage	100 - 240 VAC	
Power Consumption per Duty Cycle	1500 Watt Max	At rated output
Max Input Power Protection	+3 dBm	<10 Sec without damage
Load VSWR Protection	$\infty : 1$	Output isolator

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U
Weight	20 kg. Max	
RF Connectors In/Out	Type-N Female / WR75	Front Panel Standard
AC Power	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	

# AMP6032-1 SOLID STATE HIGH POWER AMPLIFIER

**OUTLINE DRAWING – Shown with LCD Controller Option**

