

## Communications & Power Industries Pulsed Amplifier

### Versatile

Modular assembly allows for either lower powered multiple test applications or a single amplifier phase combined system of two VZC-3530J1 amplifiers achieving 8.0 kW peak-pulsed output power.

Wide band, automatic fault recycle, user-friendly microprocessor-controlled logic with integrated computer interface, digital metering, and quiet operation suitable for laboratory environments.

An integral solid state preamplifier and IEEE interface are included as standard features.

### Global Applications

230 VAC operation. Designed to meet International Safety Standard EN61010 and Electromagnetic Compatibility 2004/108/EC. NOT subject to ITAR export controls.

### Easy to Maintain

Modular design and built-in fault diagnostic capability.

### Worldwide Support

Backed by CPI's worldwide 24-hour customer support network that includes more than 20 regional factory service centers.

With a history of producing high quality products, we can help you with your pulsed amplifier.

Contact us at [BMDMarketing@cpii.com](mailto:BMDMarketing@cpii.com) or call us at +1 978-922-6000.



### FEATURES:

- Mobile
- GPIB remote
- Touchscreen
- Waveguide output

### BENEFITS:

- Compact high pulsed power
- Single phase AC power
- Local or remote control
- Wide RF bandwidth

### APPLICATIONS:

- Test and measurement systems

# C-Band 8.0 kW TWT Pulsed Amplifier: VZC3530P2

## SPECIFICATIONS

Frequency	4.0 to 8.0 GHz
Output power (min.) flange	8000 W
Gain	66 dB min. at rated power; 70 dB typical
Gain adjustment range	20 dB min.
Input VSWR	2.5:1 typical
Output VSWR	2.5:1 typical
Load VSWR	1.5:1 max. for full spec. compliance; Any value for continuous operation (VSWR protection)
Pulsewidth	0.1 $\mu$ s to 100 $\mu$ s
PRF	50 kHz max.
Duty cycle	6% max.
Delay	400 ns typical
Droop	0.5 dB over 50 $\mu$ s
NPO	-10 dBm/MHz Beam on; -110 dBm/MHz Beam off
Primary power	220-240 VAC, single phase 47-63 Hz
Power consumption	4.0 kVA typical
Filament voltage	Reduction of 10% in standby for extended TWT life
Inrush current	200% max.
Ambient temperature	-10° to 40°C operating -40° to 70°C non-operating
Relative humidity	95% non-condensing
Altitude	10,000 ft. with standard adiabatic derating of 2°C/1000 ft., operating; 40,000 ft., non-operating
Shock and vibration	As normally encountered in a protected laboratory environment
Cooling (TWT)	Forced air with integral blower Rear air intake and exhaust; 0.10" water max. external pressure loss allowable
RF Input connection	Type N female
RF Output connection	WRD-350 waveguide flange
Dimensions (W x H x D)*	23 x 59 x 37 in. (548 x 1499 x 940 mm)
Systems weight	≈600 lbs. (273 kg)
Heat dissipation	≈3000 W
Safety	ENG61010
Acoustic noise	65 dBA @ 3 ft. from amplifier

\*excluding cabinet and system accessories



**Beverly Microwave Division**  
150 Sohier Road  
Beverly, Massachusetts  
USA 01915

tel +1 978-922-6000  
email [BMDMarketing@cpil.com](mailto:BMDMarketing@cpil.com)  
fax +1 978-922-8914  
web [www.cpii.com](http://www.cpii.com)

For more detailed information, please refer to the corresponding CPI technical description if one has been published, or contact CPI. Specifications may change without notice as a result of additional data or product refinement. Please contact CPI before using this information for system design.

©2020 Communications & Power Industries LLC. Company proprietary; use and reproduction is strictly prohibited without written authorization from CPI.