

# Impulse Wave Generator

## PG 12 - 400

**Surge voltage**  
**1.2/50  $\mu$ s**  
**0.2-12kV**

**acc. to**  
**IEC60060-1, IEC61010-1,**  
**IEC 60664-1**



The Combination Wave Generator PG 12-400 is a impulse-voltage generator which, for high-impedance loads,  $R_L > 500\Omega$ , delivers a standard impulse voltage with waveform 1.2/50 $\mu$ s.

The generator allows surge testing of components and devices, galvanic coupling of surges to cable shields, shielded enclosures and cabinets as well as testing electromagnetic compatibility, EMC, of electronic devices and systems against pulsed and conducted interference.

Executing surge immunity tests at power supply a line triggering of high-voltage pulses is accomplished synchronous with mains. The precise trigger point can be shifted between 0 to 360 ° after the zero crossing of the mains voltage. The polarity of the output voltage is selectable. Positive, negative or alternating polarity of the output voltage can be pre selected.

The PG 12-800 excels by its compact design, simple handling and precise reproducibility of test impulses. The output current- and voltage waveforms, due to built-in sensors, can be recorded via separate signal outputs for current and voltage.

PG 12-804 features a microprocessor controlled user interface and a 5" touch screen unit for ease of use. The microprocessor allows the user to execute either standard test routines or a "user defined" test sequence. The test parameters and even the settings of an external CDN, which are shown on the built in display, are easily adjusted by means of touch screen. A standard USB port provides the ability to print a summary of the test parameters to a USB stick.

Moreover, all generator functions may be computer controlled.

The software program PG-REMOTE allows full remote control of the test generator via fiber optic Ethernet interface as well as documentation and evaluation of test results, accordingly to the IEC 17025. To record definite impulses, it is equipped with an Impulse Recording Function (IRF)

TECHNICAL SPECIFICATIONS	PG 12- 400
<b>Mainframe:</b>	
Microprocessor controlled touch panel	5", 800X480, 24 bit
Optical Ethernet Interface for remote control of the generator	optional
Interface for saving reports	USB
Optical-interface for remote control of external CDN's	Built-in
External Trigger input	10 V an 1 k $\Omega$
External Trigger output	10 V an 1 k $\Omega$
Connector for external safety interlock loop and external red and green warning lamps acc. to VDE 0104	24 V = 230 V, 60W
Mains power	230 V , 50/60 Hz
Dimensions: desk top case W * H * D	453*320*520 mm <sup>3</sup>
Weight	23 kg
<b>Impulse Wave Generator acc. to IEC 60060-1</b>	
Test voltage, open circuit condition	0.2 - 12 kV $\pm$ 10 %
Voltage settings	1 V step
Waveform acc. to IEC 60060 open circuit	1.2 / 50 $\mu$ s $\pm$ 30/20 %
Waveform acc. to IEC 60060 short circuit	Not defined
Serial resistor	40 $\Omega$
Optional other serial resistors	available
Polarity of output voltage/current, selectable	pos/neg
maximum stored energy	400 Joule
charging time for max. charging voltage	< 10s
HV-output, HV plug	HV-OUT, GND
<b>Mains synchronous triggering :</b>	
Phase shifting, digitally selectable to mains supply	0 - 360 $^{\circ}$ , step 1 $^{\circ}$
Display of peak value of pulse voltage/current	built-in
Monitor output for pulse output voltage	ratio = 1000 : 1 $\pm$ 5 %
Monitor output for pulse output current	10V $\equiv$ 5 kA $\pm$ 5 %
<b>Option:</b> PG Remote software test package, running under Microsoft Windows, for the external control of the device includes 5 m long fibre optic cable and PC Ethernet Interface	
<b>Option:</b> Test pistols for large EUTs	
<b>Additional accessories available:</b> Test cabinet PA 503 / PA 505	