



5300 Beethoven Street, Los Angeles, CA 90066
 TEL: (310)306-5556 • FAX: (310)821-7413
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 6012-001
700-900 MHz
500 WATTS
RF AMPLIFIER FOR NMR

Solid State Broadband High Power RF Amplifier

The 6012-001 is a 500 Watt broadband amplifier that covers the 700-900 MHz frequency range. This amplifier utilizes linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency, pulsed operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 6012-001 comes with an extended multiyear warranty backed by Ophir RF's commitment to total customer satisfaction.

CONTROL & INDICATIONS

- ◇ AC Circuit Breaker
- ◇ TTL Control for Blanking (BNC)
- ◇ Temperature Fault

ORDERING MODELS

- ◇ R - Rear Panel Connectors
- ◇ F - Front Panel Connectors

CIRCUIT PROTECTIONS

- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage
- ◇ Open and Short Protection

<u>Electrical</u>	<u>Parameter</u>	<u>Specification @ 25° C</u>
1	Frequency Range	700-900 MHz
2	Saturated Output Power	500 Watts typical
3	Power Output @ 1dB Comp.	250 Watts min
4	Small Signal Gain	+57 dB min
5	Small Signal Gain Flatness	± 1.5 dB max
6	Blanking	TTL
7	Blanking Isolation	50dB min
8	Blanking speed	< 5uS typical
9	Input VSWR	2:1 max
10	Harmonics	-20 dBc @ 250 Watts
11	Spurious Signals	< -60 dBc typical @ 250 Watts
12	AC Input Power	3000 Watts max
13	AC Input	100 – 240 VAC, single phase
14	RF Input	0 dBm Max
<u>Mechanical</u>		
15	Dimensions	19" x 8.75" x 26"
16	Weight	110 lb. max
17	Connectors	Type-N
18	Grounding	Chassis
19	Cooling	Internal Forced Air
<u>Environmental</u>		
20	Operating Temperature	0° C to +50° C
21	Operating Humidity	95% Non-condensing
22	Operating Altitude	Up to 10,000' Above Sea Level
23	Shock and Vibration	Normal Truck Transport

Specifications subject to change without notice



F VERSION SHOWN

