



5300 Beethoven Street, Los Angeles, CA 90066  
 TEL: (310)306-5556 • FAX: (310)577-9887  
 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

**MODEL 5020**  
**500 - 1000 MHz**  
**200 WATTS**  
**LINEAR POWER RF AMPLIFIER**

### Solid State Broadband High Power RF Amplifier

The 5020 is a 200 Watt broadband amplifier that covers the 500 – 1000 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3<sup>rd</sup> order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR<sub>RF</sub> amplifiers, the 5020 comes with an extended multiyear warranty.

|                      | Parameter                  | Specification @ 25° C         |
|----------------------|----------------------------|-------------------------------|
| <b>Electrical</b>    |                            |                               |
| 1                    | Frequency Range            | 500 – 1000 MHz                |
| 2                    | Saturated Output Power     | 200 Watts typical             |
| 3                    | Power Output @ 1dB Comp.   | 100 Watts min                 |
| 4                    | Small Signal Gain          | +53 dB min                    |
| 5                    | Small Signal Gain Flatness | ± 1.5 dB max                  |
| 6                    | IP <sub>3</sub>            | +56 dBm typical               |
| 7                    | Input VSWR                 | 2:1 max                       |
| 8                    | Harmonics                  | -20 dBc typical @ 100 Watts   |
| 9                    | Spurious Signals           | > -60 dBc typical @ 100 Watts |
| 10                   | Input/Output Impedance     | 50 Ohms nominal               |
| 11                   | AC Input Power             | 1500 Watts max                |
| 12                   | AC Input                   | 100 – 240 VAC, single phase   |
| 13                   | RF Input                   | 0 dBm max                     |
| 14                   | RF Input Signal Format     | CW/AM/FM/PM/Pulse             |
| 15                   | Class of Operation         | AB                            |
| <b>Mechanical</b>    |                            |                               |
| 16                   | Dimensions                 | 19" x 7.0" x 20"              |
| 17                   | Weight                     | 60 lb. max                    |
| 18                   | Connectors                 | Type-N                        |
| 19                   | Grounding                  | Chassis                       |
| 20                   | Cooling                    | Internal Forced Air           |
| <b>Environmental</b> |                            |                               |
| 21                   | Operating Temperature      | 0° C to +50° C                |
| 22                   | Operating Humidity         | 95% Non-condensing            |
| 23                   | Operating Altitude         | Up to 10,000' Above Sea Level |
| 24                   | Shock and Vibration        | Normal Truck Transport        |

Specifications subject to change without notice.

### CIRCUIT PROTECTIONS

- ◇ Thermal Overload
- ◇ Over Current
- ◇ Over Voltage

### ORDERING MODELS

- ◇ R - Rear Panel Connectors
- ◇ F - Front Panel Connectors
- ◇ RE - R model w/Control Option
- ◇ FE - F model w/Control Option
- ◇ RT - RE model w/Ethernet Interface
- ◇ FT - FE model w/Ethernet Interface



**FE Model Shown**