

5300 Beethoven Street, Los Angeles, CA 90066 TEL: (310)306-5556 • FAX: (310)577-9887 WEB: www.ophirrf.com • E-MAIL: sales@ophirrf.com

MODEL 5087

10 kHz - 200 MHz 250 WATTS LINEAR POWER RF AMPLIFIER

Solid State Broadband High Power RF Amplifier

The 5087 is a 250 Watt broadband amplifier that covers the 10 kHz – 200 MHz frequency range. This small and lightweight amplifier utilizes Class A/AB linear power devices that provide an excellent 3rd order intercept point, high gain, and a wide dynamic range.

Due to robust engineering and employment of the most advanced devices and components, this amplifier achieves high efficiency operation with proven reliability. Like all OPHIR_{RF} amplifiers, the 5087 comes with an extended multiyear warranty.

D ,	0 '' '' 0 050 0
<u>Parameter</u>	Specification @ 25° C
Frequency Range	0.01 – 200 MHz
Saturated Output Power	250 Watts typical
Power Output @ 1dB Comp.	200 Watts min
Small Signal Gain	+55 dB min
Small Signal Gain Flatness	<u>+</u> 2.0 dB max
IP ₃	+60 dBm typical
Input VSWR	2:1 max
Harmonics	-20 dBc typical @ 200 Watts
Spurious Signals	> -60 dBc typical @ 200 Watts
Input/Output Impedance	50 Ohms nominal
AC Input Power	1200 Watts max
AC Input	100 – 240 VAC, single phase
RF Input	0 dBm max
RF Input Signal Format	CW/AM/FM/PM/Pulse
Class of Operation	AB
Dimensions	19" x 8.75" x 20"
Weight	80 lb. max
Connectors	Type-N
Grounding	Chassis
Cooling	Internal Forced Air
Operating Temperature	0° C to +50° C
Operating Humidity	95% Non-condensing
Operating Altitude	Up to 10,000' Above Sea Level
Shock and Vibration	Normal Truck Transport
	Saturated Output Power Power Output @ 1dB Comp. Small Signal Gain Small Signal Gain Flatness IP3 Input VSWR Harmonics Spurious Signals Input/Output Impedance AC Input Power AC Input RF Input RF Input Signal Format Class of Operation Dimensions Weight Connectors Grounding Cooling Operating Temperature Operating Humidity Operating Altitude

Specifications subject to change without notice.

CIRCUIT PROTECTIONS

- ♦ Thermal Overload
- ♦ Over Current
- ◊ Over Voltage

ORDERING MODELS

- ♦ R Rear Panel Connectors
- ◊ F Front Panel Connectors
- ♦ RE R model w/Control Option
- ♦ FE F model w/Control Option
- ♦ RT RE model w/Ethernet Interface
- ♦ FT FE model w/Ethernet Interface

