



EMI Shielded Tents and Electrically Thin Shielded Rooms

Select Fabricators, Inc.

Products for this millennium

Portable EMI Shielding Tents—Assembly Instructions

Model #7006 Aluminum Frame

To Assemble

1. Expand the EZ-up frame on a flat, clean surface. Insert side poles and secure at the second hole from the top. See photo on the right.
2. Spread the tent out in the middle structure with the connector loops on top. Make sure the door is opened slightly and tucked inside.
3. With frame partially assembled as in Figure 1, use the bungee cords to attach the top center of the tent to the frame, then the other 4 top bungee cords. Refer to the Figure 2 for bungee attachment. Work your way around the tent to make sure all outside top cords are attached. Attach the bungee cords on the bottom of the upper frame.
4. Attached the remaining bungee cords to secure the tent sides then expand the frame to erect the tent.



Figure 1





Figure 2



Bungee Attachment Points



Steps 3 and 4



Step 5



To Disassemble

1. Remove any battery packs.
Leave (optional) lights inside tent.
2. Detach tent from frame.
3. Fold in tent side with vents (if any).
Protect vent with sleeve or other material.
4. Fold side back on itself and pull the loops out.
5. Lay tubes and sleeves within the folds of the tent back.
6. With the door facing you, fold one side in about halfway.
7. Fold the other side in with enough overlap to fit the tent in the bag.
8. Fold one end up about 1/3 of length to fit tent into bag.

Select Fabricators, Inc.
+1.585.393.0650

©2006Select Fabricators, Inc. Rmdfu0011 rev.1

Fax: 1.585.393.1378
eMail: oselectf@rochester.rr.com
www.selectfabricatorsinc.com