

- High-hiding tintable formula
- Excellent protection barrier between wallcovering and surface
- Bonds to glossy surfaces without sanding
- Promotes strippability

Dynamite[®] 222 White Acrylic Primer & Sizing is a premium-grade water-based wallcovering primer and sizing that properly prepares a wide range of surfaces prior to hanging any type of wallcovering, including pre-pasted materials. It has excellent hiding power that easily covers existing paint, wallcovering patterns, or color variations in the wall surface. This product can be tinted to match the background color of the wallcovering to avoid visible seams. **Dynamite[®] 222** provides a long-lasting protection barrier between the wallcovering and the wall surface. It protects the drywall like an oil-based primer and adheres to glossy surfaces like an acrylic primer.

SURFACE PREPARATION: Surface to be primed must be clean, dry, smooth and structurally sound. Clean wall to remove dirt, grease, wax, paste residue and loose paint with **Dynamite[®] All-Purpose Cleaner**. Rinse with clean water. Repair surface damage with **Dynamite[®] Non-Shrink Spackling**.

TINTING: To avoid visible seams, primer can be tinted to match background color of wallcovering (maximum of 2 fl.oz. of universal tinting color/gallon).

APPLICATION: Thoroughly mix before using. DO NOT DILUTE. Apply evenly to wall surface using a paint brush, roller or sprayer. Allow surface to dry 2 hours before hanging wallcovering. Do not apply when temperature is below 45 °F. Clean up with warm water immediately after application. Proceed hanging wallcovering according to manufacturer's instructions.

COVERAGE: One gallon covers approximately 400 sq. ft. Coverage rate can vary dependent on the condition of the substrate, method of application and weather conditions.

PRECAUTIONS: Do not store at temperatures above 100 °F or below 40 °F. KEEP FROM FREEZING. This product is not intended for long term storage once pail is opened and a portion of its contents used. When transporting this product, ensure that lid is tight and pail secure and upright. Do not allow pail to tumble as this may cause lid to loosen and leakage to occur. Do not transport on passenger seats or inside the passenger compartment of any vehicle. Store product in the cargo area of vehicle, and secure over protective cloths to prevent damage due to accidental spills. Do not reuse empty containers. Do not use in drinking water or food systems.

CLEAN-UP: Cleans with water when wet.

QUALITY PROMISE: Gardner-Gibson, Inc. promises that this product, when applied in accordance with our written directions in applications recommended by us as suitable for this product, will be free of defects in material. In the unlikely event that a defect should develop, and you notify us of such a defect within 12 months of purchasing product, and provide adequate proof of purchase, we will replace the defective product at no cost to you. This promise of quality is the sole and exclusive remedy for any such defective product. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING THE WARRANTIES OF MERCHANTABILITY AND/OR FITNESS FOR ANY PARTICULAR USE OR PURPOSE AND GARDNER-GIBSON, INC. WILL IN NO EVENT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES.

AVAILABLE SIZES						
PRODUCT CODE	UNIT SIZE	UNIT DIMENSIONS	FILL LEVEL	UNIT WEIGHT	PACK	UPC
7222-3-20	1 gal.	7.625" x 7.625" x 7.875"	3.6 qt. / 3.4 L	10.5 lbs.	4/case	027134722226
7222-3-30	5 gal.	12.5" x 12" 14.75"	5 gal. / 18.9 L	55 lbs.	1 ea.	027134722233