



SCIF-USx Warranted RF Shielded Floor System for ICD / ICS 705 SCIF Rooms

Using Xalon XFS60 (60dB) or XFS80 (80 dB) Proprietary Floor Systems
Uzin Utz Warranties the Floor System structure, 4 to 12 layers required.

Layer	Layers (Top to Bottom)	Comments	Product(s)
Top Wear Layer	Finished Flooring	Ready for final flooring to be applied, just like you would on to standard concrete floor.	Vinyl Composite Tile, ESD Tile, Carpet, ESD Carpet Polished Concrete, etc.
Twelve (12)	Apply SCIF TEXAS Fiber-Reinforced Concrete Level RF Shielded Floor System	Apply Uzin SCIF TEXAS self-leveling product to the desired depth. Let dry.	UZIN SCIF TEXAS Fiber Reinforced Self-Leveling Compound
Eleven (11)	Apply Uzin SCIF COLORADO primer.	Apply coat of Uzin SCIF COLORADO. Let dry.	UZIN SCIF COLORADO Non-Porous Primer
Ten (10)	Apply Surface Strengthener / Moisture Vapor Reducer	Apply coat of Uzin SCIF NEW JERSEY. Let dry.	UZIN SCIF NEW JERSEY Moisture Isolation Barrier
Nine (9)	Install 2 nd XFS panels offset 2' x 2' from 1 st XFS panels already glued down and seam taped	Install 2 nd Layer of XFS panels with Uzin SCIF ALABAMA Adhesive	XFS60 (60dB) or XFS80 (80dB) Panels
Eight (8)	Apply Uzin SCIF ALABAMA 2 Part Urethane Adhesive	Apply XFS panels using Uzin SCIF ALABAMA two-part urethane adhesive. Let dry.	UZIN SCIF ALABAMA 2-Component Polyurethane Adhesive
Seven (7)	Install Xalon 4" wide RF shielded seaming tape	Seam Tape the Xalon XFP Panels	Xalon Proprietary Copper Seaming Tape XFT14 or XFT50
Six (6)	Install Xalon XFL Perimeter L-Flashing 4" minimum on the floor.	Vertical part can be screwed to wall studs with clear zinc coated screws Horizontal part can be seam taped to the top of the 1 st layer of XFS panels	Install Grabber Clear Zinc Coated Screws (for walls) Seam Tape XFL L-Flashing to XFS Panels With the XF14 or XFT50 Seaming Tape
Five (5)	Install Xalon XFP60 or XFP80 RF 4' x 4' Shielded Panels & Tape 4' x 4' XFP Shielding Panels	Install 1 st Layer of XFS60 panels with Uzin SCIF ALABAMA adhesive	Xalon XFP60 or XFP80 Panels
Four (4)	Apply Uzin SCIF ALABAMA 2 Part Urethane Adhesive	Apply XFP60 or XFP80 panels using Uzin SCIF ALABAMA two-part urethane adhesive.	UZIN SCIF ALABAMA 2-Component Polyurethane Adhesive

1-303-761-9447 www.ramayes.com or 1-833-XalonRF (833.925.6673) www.xalonrf.com

©2026 RA Mayes Company & Xalon RF Shielding Systems. Unauthorized distribution is prohibited.



		Let dry.	
Three (3)	Apply Uzin SCIF TEXAS self-leveling	Apply Uzin leveling product to flatten the floor to accept the metal panels. Let dry.	UZIN SCIF TEXAS recommended for most applications
Two (2)	Apply Uzin SCIF COLORADO primer.	Apply primer Let dry.	UZIN SCIF COLORADO Non-Porous Primer
One (1)	Apply Uzin SCIF MISSOURI Moisture Vapor Retarder / Surface Strengthener	Apply 2-part Epoxy This will address any moisture vapor in or below the slab. Let dry.	UZIN SCIF MISSOURI Moisture Vapor Retarder / Surface Strengthener
Bottom Base Layer	Existing Concrete Floor	Raw Concrete	Existing Concrete Floor

Floor flatness is FF of 35 to 50 <https://dipstick.com/>

The final wear layer floor material and adhesive will be warranted by that product's manufacturer.

*The Xalon EMI-SHIELD **AL5 RF Shielded Seaming Tape** may be used in this system, with prior written approval.

Xalon XFS60 is the most economical 60dB solution.

Xalon XFS80 is the most economical 80dB solution.

Substitute Uzin or Xalon products VOIDs the warranty.

The system layers can be modified or deleted with prior written approval by Uzin.

Some RF shielded floor systems may only require two layers.

Any written warranty must come from Uzin.

*** The RF shielded floor system must be installed by a Xalon/Uzin prequalified floor contractor, to get the Uzin warranty. Prequalified floor contractors are available in all 50 states and in most countries.**



04/01/2026

1-303-761-9447 www.ramayes.com or 1-833-XalonRF (833.925.6673) www.xalonrf.com

©2026 RA Mayes Company & Xalon RF Shielding Systems. Unauthorized distribution is prohibited.



SCIF-USx ICD 705 Warranted RF Shielded Floor Questionnaire

Using Uzin and Xalon XFS60 or XFS80 Proprietary Metal Panels with RF Seaming Tape

Circle, highlight or write your answers

1) What is the RF shielding effectiveness level required at 10GHz, in dB?

(60dB, 80dB, Other _____)

2) Is the RF shielding effectiveness frequency range specified?

EX 10MHz to 10GHz (_____)

3) What floor level will the RF shielded SCIF room be installed?

(Below ground level, Ground level, Above ground level, Floor level _____)

4) If the existing floor is slab on grade concrete, is there a moisture vapor retarder installed below the concrete slab?

(YES, NO, NEW CONSTRUCTION), if YES (Class I, II or III)

5) What is the parent room existing floor substrate material?

(Existing Concrete, New Concrete, Wood, Metal, Other _____)

6) Floor must be clean, dry, smooth, ASTM F710 and flat per FF/FL number of 35 to 50. Visit the Flat Floor Library at www.Dipstick.com for More Help Do you know the FF number of the floor?

(Yes, the FF is _____ No, but can get it ____ I need someone else to measure it _____)

7) What is required to be repaired on the existing floor?

(Patching, Self-leveling, Moisture Mitigation, Waterproofing, Mechanical Adhesive Removal, Other _____)

8) What are the concrete Relative Humidity & Ph numbers?

(RH: _____ Ph: _____)

9) What are the floor load requirements?

(Foot traffic, Rolling desk chairs, Pallet jacks, Forklifts, MFG equipment, Robotics, Vehicles, Trucks, Other _____) Is maximum PSI known: _____



10) Are there any floor drains or waste pipe going through the floor?

(YES, NO)

11) Are there any other penetrations or feeds in the floor?

(AC/DC Power Lines, PVC pipe, fiber-optic lines, telephone lines, Other: _____)

12) Is the existing concrete non-porous

(If YES, the reason why _____)

13) Does the floor system require anchors, threaded rod or other hardware installed in it?

EX RAF pedestals (Describe _____)

14) Are you required to RF shield the entire SCIF floor vs. just bringing the RF shielding 1 to 3 feet out on to the floor?

(YES, NO)

15) Is there an RF shielded SCIF within the perimeter of a larger RF shielded SCIF?

(YES, NO)

16) What is the application of the RF shielded ICD 705 SCIF area?

(Clean rooms, Manufacturing, Computer rooms, Offices, Research and Development, Control rooms, Meeting rooms, Other _____)

17) What is the wear layer of flooring?

(ESD tile, ESD carpet, Regular carpet, VCT, PVC / plastic, Rubber, Epoxy, Other _____) installation will require? (Floating / interlocking, Adhesive, Primers, Copper grounding systems, Other _____)

18) What is the manufacturer and model of the wear layer flooring?

(_____, _____)

19) What is the wear layer flooring adhesive?

(_____) Include data sheets if possible



Name of Project: _____

State: _____

Square Footage of RF Shielded Flooring: _____

Linear Footage of Perimeter Wall Shielding _____ (for tying floor shielding to wall shielding)

Name of Contractor: _____

Ship to Address of Contractor: _____

Point of Contact: _____

Contact Phone: _____

Contact Email: _____

Do you need a quote for the fully installed warranted SCIF-USx RF shield floor system? (YES, NO)

Do you need a quote for the fully installed floor, walls and ceiling? (YES, NO)

Email this completed questionnaire to sales@ramayes.com

Subject: Send us a quote on the SCIF-USx warranted RF shielded floor system

4/1/2026