



## AMP2012CA-LC SOLID STATE HIGH POWER AMPLIFIER

### FEATURES

Rack mounted system  
 Class A/AB linear LDMOS design  
 Instantaneous RF & VHF band wide bandwidth coverage  
 Suitable for all single channel modulation standards  
 Built-in protection circuits  
 High reliability and ruggedness



### ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	2 - 250 MHz	
Power Output @ P1dB	1300 Watt Typ	CW
Power Gain	60 dB Min	
Power Gain Flatness	3.0 dB p-p Max	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	50dBm/Tone, Δ = 1MHz
Harmonics	-20 dBc Typ	
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	180 - 240 VAC	
Power Consumption	5000 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

### ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

### MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 354 x 820 mm	8U - excluding handles
Weight	45 Kg. Max	
RF Connectors In/Out	Type-N Female/ Type-7/16 Female	Front or rear panel
AC Power	IEC 60320-C14 / 9-Pin D-Sub	Or equivalent
Cooling	Quiet Cool Hybrid Air/Liquid	Variable speed
<b>STANDARD:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Remote Bluetooth application Optional

## OUTLINE DRAWING

