



AMP2024A SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Class AB linear LDMOS design
- Instantaneous ultra-wide bandwidth
- Designed for broadband EMI/RFI, Lab, Comm. and EW applications
- Suitable for CW, pulse and all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS 25°C, 50Ω

Parameter	Specification	Notes
Operating Frequency Range	20 - 1000 MHz	
Power Output @ Psat	200 Watt Min	CW
Power Output @ P1dB	120 Watt Min	
Power Gain	53 dB Min	Pin=0dBm for nominal Pout
Power Gain Flatness	4.0 dB p-p Max	Constant input power
2-Tone Intermodulation (IMD)	-25 dBc Typ	43dBm/Tone, Δ = 1MHz
Input Return Loss	-10 dB Max	Relative to 50 Ohm
Harmonics	-20 dBc Typ	At rated output power
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	100 - 240 VAC±10%	50/60 Hz ±6%
Power Consumption	1000 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 Minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 133 x 560 mm	3U - Excluding handles
Weight	20kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Remote Bluetooth application

AMP2024A SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

