



AMP2036-1DB SOLID STATE HIGH POWER AMPLIFIER



FEATURES

- Redundant X & Ku-Bands Rack mount system
- Class AB linear GaN design
- Instantaneous wide bandwidth
- Suitable for CW, pulse, and all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	8.0 - 18.0 GHz	
Power Output @ Psat	20 Watt Min	Pulse or CW mode
Power Output @ P1dB GCP	12 Watt Typ	CW
Power Gain	43 dB Min	
Gain Adjustment Range	10 dB Min	Manual or Remote
Power Gain Flatness	4.0 dB p-p Max	
Input Return Loss	12 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	33dBm/Tone, $\Delta = 1\text{MHz}$
Noise Figure	10 dB Max	
Harmonics	>20 dBc Typ	At rated output power
Non Harmonics Spurious	>60dBc	
Operating Voltage	180 - 240 VAC	Single phase
Power Consumption	800 Watt Max	Both HPA on , at Rated Pout
Max Input Power Protection	+3 dBm	<10 Seconds
Load VSWR Protection	$\infty : 1$	<1 Minute
Pulse Rise / Fall Time	50 nS Max	
RF Delay	120 nS Max	
Pulse Blanking Output Power Density	<-130 dBm (2 KHz BW)	TTL (0-5V), Impedance >1k Ω

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	19" x 7" x 22" (483 x 178 x 580 mm)	4U
Weight	30 Kg.	
RF Connectors In/Out	Type-SMA Female	Rear panel
Pulse Blanking Connector	BNC Female	Rear panel
HPA 1 or 2 Selector		
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	Rear Panel
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Control: FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, Optional GPIB Interface	Remote Bluetooth application



**AMP2036-1DB
SOLID STATE HIGH POWER AMPLIFIER**



**AMP2036-1DB
SOLID STATE HIGH POWER AMPLIFIER**

OUTLINE DRAWING