



## AMP2043P SOLID STATE HIGH PULSE POWER AMPLIFIER

### FEATURES

- Small form factor rack-mounted system
- Class AB linear GaN design
- Instantaneous L-Band octave bandwidth
- Suitable for linear high peak pulse applications
- Built-in protection circuits
- High reliability and ruggedness



### ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification				Notes
Model	AMP2043P-05K	AMP2043P-1K	AMP2043P-2K	AMP2043P-4K	
Operating Frequency Range	1.0 - 2.0 GHz				
Power Output @ Peak Pulse	500 Watt Min	1 KW Min	2.0 KW Min	4.0 KW Min	Peak Pulse
Input Pulse Characteristics	<b>Width</b>	<b>Duty</b>	<b>PRF</b>	<b>Droop</b>	
	5 - 100 μS	5 % Max	1.0 - 10 KHz	<1 dB	
Power Gain	57 dB Min	60 dB Min	63 dB Min	66 dB Min	
Power Gain Flatness	2.0 dB p-p Max				Constant input power
Input Return Loss	-10 dB Max				Relative to 50 Ω
Noise Figure	6 dB Max				
Output Power On/Off Ratio	-90 dB Max				TTL Gate Control
Harmonics	<-20 dBc Typ				At rated output power
Spurious	-60 dBc Max				Non-harmonics
Operating Voltage	100 - 240 VAC				50 - 60Hz
Power Consumption	250 Watt Max	400 Watt Max	800 Watt Max	1.5 KW Max	At rated Pout
Input Power Protection	+8 dBm Max				<10Sec without damage
Load VSWR	Full spec @ 1.5 : 1 & Operational @ 2 : 1				



## AMP2043P SOLID STATE HIGH PULSE POWER AMPLIFIER


### ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing


### MECHANICAL SPECIFICATIONS

Parameter	Specification				Notes
Dimensions W x H x D	3U	3U	5U	8U	Rack mount chassis
Weight	20 Kg	20 Kg	30 Kg.	40 Kg.	
RF Connectors In / Out	Type-N F	Type-N F	Type-N F / DIN		
AC Power / Interface Connector	MS / D-Sub				
Cooling	Built in Fan Cooling				Variable speed
<b>Optional</b> Digital Monitor & Control: FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, USB, RS422/485, USB Optional GPIB Interface				

## OUTLINE DRAWING - 3U



## OUTLINE DRAWING - 5U



## OUTLINE DRAWING - 8U

