



AMP2064 SOLID STATE HIGH POWER AMPLIFIER



FEATURES

- Rack mounted system
- Class AB linear GaN design
- Instantaneous wide bandwidth
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness

ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	0.8 - 3.1 GHz	
Power Output @ Psat	420 Watt Min	CW
Power Output @ P1dB	400 Watt Min	
Input Power for rated Output	-3.4 dBm Nom	
Power Gain	59 dB Nom	
Gain Adjustment Range	15 dB Min	
Power Gain Flatness	5.0 dB p-p Max	Constant input power
Input Return Loss	10 dB Min	Relative to 50 Ohm
Harmonics	2 nd : -15 dBc Typ 3 rd : -20 dBc Typ	At rated output power
Spurious	-80 dBc Max @ Δ = 100 KHz	Non-harmonics
Operating Voltage	100 - 240 VAC ±10%	50/60 Hz ±6%
Power Consumption	2800 Watt Max	At rated Pout
Input Power Protection	+15 dBm Max	
Load VSWR Protection	∞ : 1	<1 Minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS


Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	19" x 7" x 22" (483 x 178 x 560 mm)	R4U
Weight	65 lb. Max	
RF Connectors In / Out	Type-N Female	Front Panel Standard
Forward and Reflected Sample Ports	Typ-N Female	Front panel
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	Variable speed
Dual Interlock		
Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485 Optional GPIB Interface	Remote Bluetooth application

AMP2064 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING



- *. NOTE**
1. 4U, 4.3" LCD.
 2. RF IN/OUT Connector : N type Female
 3. AC Connector : IEC 60320-C14