



AMP2071A-LC SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class A/AB linear LDMOS design
- Instantaneous ultra-wide bandwidth
- Rack mounted system
- Designed for broadband EMI/RFI, Lab, Comm. and EW applications
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 25°C, 50Ω

Parameter	Specification	Notes
Operating Frequency Range	80 - 1000 MHz	
Power Output @ Psat	750 Watt Min	1 KW Min @ 80 - 500 MHz
Power Output @ P1dB GCP	600 Watt Typ	
Power Gain	60 dB Min	Pin=0dBm for nominal Pout
Power Gain Flatness	3.0 dB p-p Max	
Input Return Loss	-10 dB Max	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	47dBm/Tone, Δ = 1MHz
Noise Figure	10 dB Max	At full gain
Harmonics	-20 dBc Max	
Spurious	-60 dBc Max	Non-harmonic
Operating Voltage	180 - 240 VAC Single Phase	50 - 60Hz
Power Consumption	4000 Watt Max	At rated Pout
Input Power Protection	+8 dBm Max	<10 Sec without damage
Load VSWR Protection	6 : 1 Max	Auto shutdown at >6 : 1 load VSWR

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 222 x 560 mm	5U - Excluding handles
Weight	40 Kg. Max	
RF Connectors In/Out	Type-N Female / 7/16-F	Front or rear panel
AC Power / Monitoring Connectors	IEC 60320-C14 / 9 Pin D-Sub	Or equivalent
Safety Interlock Connector	15-Pin Subminiature D-Sub	
Cooling: Built in Quiet-Cool	60 dBa Typ	Close circuit liquid cooling
EMI SERIES: Digital Monitor & Control	Ethernet RJ-45 TCP/IP, RS-232, USB	Optional
FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Optional GPIB/IEEE Interface	Remote Bluetooth application

AMP2071A-LC SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

