



# AMP2095 SOLID STATE HIGH POWER AMPLIFIER

## FEATURES

Small and light weight bench-top chassis  
 Class AB linear GaN design  
 Instantaneous ultra-wide bandwidth  
 Suitable for all modulations standards  
 Built-in protection circuits  
 High reliability and ruggedness



## ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	20 - 2500 MHz	
Power Output	10 Watt Min	Saturated CW
Power Gain	40 dB Min	
Power Gain Flatness	4.0 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	33dBm/Tone, $\Delta = 1$ MHz
Harmonics	>20 dBc Typ	At rated Pout
Non Harmonics Spurious	60 dBc Min	Non Harmonics
Operating Voltage	100 - 240 VAC	
Power Consumption	100 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	$\infty : 1$	

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	265 x 88 x 229 mm	Bench Top
Weight	8 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	
<b>OPTIONAL:</b> Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, GPIB Interface, remote Bluetooth application	Available in a R2U chassis

# AMP2095 SOLID STATE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

