

AMP3127 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Class AB linear LDMOS design
- Instantaneous bandwidth
- Suitable for all single channel modulation standards
- Built-in monitoring and protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	700 - 800 MHz Min	
Power Output @ Psat	200 Watt Min	CW
Power Gain	53 dB Min	
Power Gain Flatness	2.0 dB p-p Max	
Input Return Loss	10 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	-30 dBc Typ	43dBm/Tone, $\Delta = 1\text{MHz}$
Harmonics	-30 dBc Max	At rated Pout
Non-Harmonics Spurious	-60 dBc Max	
Operating Voltage	32 VDC	
Current Consumption	18 Amp Max	At rated Pout
Max Input Power	+5 dBm	Without damage
Load VSWR Protection	$\infty : 1$ Min	
Turn On / Off Speed	5 μSec Max	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Case Temperature	-20 to +75 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions	Option 101: 200 x 120 x 28 mm	Excluding Connectors
Weight	750 gr.	Typical Weight
RF Connectors In/Out	SMA-F / Type-N	
DC Power / Interface Connector	7-Pin Hybrid D-Sub	
Cooling	External Heatsink	Forced air required

D-SUB CONNECTOR PIN ASSIGNMENT

Pin	Function	Description
1	FWD	Option-101 - Analog Forward Power Indicator
2	VVA	Option-103 - Analog Gain Control
3	CURRENT SENSOR	$I_b@20\text{mV}/100\text{mA}$ Typ
4	TEMP SENSOR	$V_T@10\text{mV}/^\circ\text{C} + 500\text{mV}$ Typ
5	SHUTDOWN	TTL
A1	VDD	32VDC
A2	GND	Ground

AMP3127 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

