



# AMP4060P-1 SOLID STATE PULSE HIGH POWER AMPLIFIER

## FEATURES

- High power GaN pulse devices
- Suitable for X-Band linear pulse applications
- Built-in Ethernet Control and Protection circuits
- High reliability and ruggedness

## ELECTRICAL SPECIFICATIONS

Parameter	Specification			Notes
Operating Frequency Range	9.2 - 10 GHz			
Peak Output Power	8000 Watt Min			5% Duty Cycle
Input Power	+9 dBm Nom			Pulsed for normal operation
Saturated Gain	60 dB Min			
Gain Adjustment Range	20 dB Min			
Power Gain Flatness	2 dB p-p Max			
Gain Stability	0.5 dB p-p Max			Constant Temperature
Pulse Characteristics	<b>Duty</b>	<b>Width</b>	<b>PRF</b>	
	5 % Max	0.2 - 50 $\mu$ Sec	10 KHz Max	
Pulse Droop	0.5 dB Max			@ 50 $\mu$ Sec
Rise / Fall Time	50 nSec			
Input / Output VSWR	2 : 1 Min			Relative to 50 Ohm
Harmonics	-10 dBc Max			
Spurious	-50 dBc Max			Non-harmonics
Noise Figure	35 dB Max			
Load VSWR Protection	2.5 : 1			Without damage
Maximum Input Power Protection	+13 dBm Max			<10Sec
Gate Control Inputs	TTL - gating pulse must precede RF by 2 $\mu$ Sec			
AC Input Voltage	230 VAC, 1 Phase, 50 - 60 Hz			
RF Output Sample	-60 dB			RF output

## ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50°C	
Vibrations	MIL-STD 810G, Method 514.6	
Altitude	10,000 feet	30,000 feet non-operating
Relative Humidity	Up to 95 %	Non-condensing

## MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	See preliminary outline drawing	12U, 19" rack
Weight	TBD	
RF Input Connector	SMA (F) Jack	
RF Output Connector	WR-90 Waveguide flange	Waveguide pressure sensor
RF Sample Port	SMA (F) Jack	
AC Power	MS3122E14-5P	or similar
Transmit Gating Connector	BNC-F	
Monitor & Control	Ethernet RJ-45 circular connector TCP/IP RS422/485 D-sub 9S port for redundancy	
Cooling	Built in Fan Cooling	Front Inlet, Rear outlet

# AMP4060P-1 SOLID STATE PULSE HIGH POWER AMPLIFIER

## OUTLINE DRAWING

