



AMP6010 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

Small and light weight bench top chassis
 Class AB linear GaN hybrid design
 Suitable for all modulations standards
 Built-in protection circuits
 High reliability and ruggedness



ELECTRICAL SPECIFICATIONS

Parameter	Specification	Notes
Operating Frequency Range	11.95 GHz \pm 250 MHz	
Power Output	20 Watt Min / 30Watt Typ	CW
Power Gain	45 dB Min	
Power Gain Flatness	1.0 dB p-p Max	
Input Return Loss	12 dB Min	Relative to 50 Ohm
2-Tone Intermodulation (IMD)	>30 dBc Typ	33dBm/Tone, Δ = 1MHz
Harmonics	>30 dBc Typ	At rated Pout
Non Harmonics Spurious	60 dBc Min	Non Harmonics
Noise Figure	10 dB Max	
Operating Voltage	100 - 240 VAC	50/60Hz
Power Consumption	160 Watt Max	At rated Pout
Max Input Power	+8 dBm	Without damage
Load VSWR Protection	5 : 1	

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non Condensation

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	265 x 88 x 229 mm	2U
Weight	8 kg.	
RF Connectors In/Out	Type-N Female	
AC Power / Interface Connector	IEC 60320-C14 / 9-Pin D-Sub	
Cooling	Built in Fan Cooling	

AMP6010 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

