



AMP6039 SOLID STATE HIGH POWER AMPLIFIER

FEATURES

- Rack mounted system
- Class AB linear LDMOS design
- High power UHF narrow-band
- Suitable for all single channel modulation standards
- Built-in protection circuits
- High reliability and ruggedness



ELECTRICAL SPECIFICATIONS: 50Ω, 25°C

Parameter	Specification	Notes
Operating Frequency Range	1.3 GHz ±1 MHz Nom	
Power Output @ Saturation	1 KW Min	CW
Power Gain	60 dB Min	0 dBm for Nom Pout
Gain Variation Over Temperature	±1.0 dB Max	
Input / Output Return Loss	-10 dB Max	Relative to 50 Ohm
3 rd Order Intercept Point (IP3)	+65 dBm	@ IMD = -30dBc
Harmonics	-20 dBc Max	At rated output
Spurious	-60 dBc Max	Non-harmonics
Operating Voltage	220 VAC Nom	
Power Consumption	5 KW Max	At rated output
Input Power Protection	+5 dBm Max	<10 Sec without damage
Load VSWR Protection	5 : 1 Max	<1 minute at rated Pout

ENVIRONMENTAL CHARACTERISTICS

Parameter	Specification	Notes
Operating Ambient Temperature	0 to +50 °C	
Storage Temperature	-40 to +85 °C	
Relative Humidity	5 to 95 %	Non-condensing

MECHANICAL SPECIFICATIONS

Parameter	Specification	Notes
Dimensions W x H x D	430 x 222 x 560 mm	5U excluding connectors
Weight	35 Kg. Max	
RF Connectors In/Out	Type-N Female / 7/16 DIN	Front or rear panel
AC Power / Interface	MS Type / 9-Pin D-Sub	Or equivalent
Cooling	Built in Fan Cooling	Variable speed
OPTIONAL: Digital Monitor & Control FWD, REV, VSWR, GAIN, ALC, V & I, TEMP	Ethernet RJ-45 TCP/IP, RS422/485, USB Optional GPIB Interface	Remote Bluetooth application

AMP6039 SOLID STATE HIGH POWER AMPLIFIER

OUTLINE DRAWING

